

NSCSANN015PGUNV

NSCSANN015PGUNV Information



For Reference Only

Part Number NSCSANN015PGUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 4-SIP, Side Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSCSANN015PGUNV Specifications

Manufacturer Part NumberNSCSANN015PGUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP, Side PortSeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 77.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Side PortSupplier Device Package4-SIP		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP, Side Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 77.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Manufacturer Part Number	NSCSANN015PGUNV
Package 4-SIP, Side Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 77.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP, Side Port Series TruStability? NSC Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 77.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 77.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Side PortSupplier Device Package4-SIP		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 77.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Side PortSupplier Device Package4-SIP	Package	4-SIP, Side Port
Operating Pressure Output Type Wheatstone Bridge Output OmV ~ 77.5 mV (5V) Accuracy ±0.25% Voltage - Supply Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package 4-SIP	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput0 mV ~ 77.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Side PortSupplier Device Package4-SIP	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 77.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP}$, Side PortSupplier Device Package $4-\text{SIP}$	Operating Pressure	15 PSI (103.42 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeatures-Termination StylePC PinMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP}$, Side PortSupplier Device Package $4-\text{SIP}$	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package	Output	$0 \text{ mV} \sim 77.5 \text{ mV} (5\text{V})$
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Accuracy	±0.25%
Port Style Barbed Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Port Size	Male - 0.19" (4.93mm) Tube
Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Port Style	Barbed
Maximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP , Side PortSupplier Device Package 4-SIP	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Termination Style	PC Pin
Package / Case 4-SIP, Side Port Supplier Device Package 4-SIP	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP, Side Port
Report errors?	Supplier Device Package	4-SIP
		Report errors?

NSCSANN015PGUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSCSANN015PGUNV Payment Methods



















NSCSANN015PGUNV Shipping Methods













If you have any question about NSCSANN015PGUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com