

NSCSMNN150PDUNV

NSCSMNN150PDUNV Information



For Reference Only

Part Number NSCSMNN150PDUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS DIFF 150PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSCSMNN150PDUNV Specifications

Manufacturer Part NumberNSCSMNN150PDUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeriesTruStability? NSCPressure TypeDifferentialOperating Pressure±150 PSI (±1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 258.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure±250 PSI (±1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series TruStability? NSC Pressure Type Differential Operating Pressure ±150 PSI (±1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 258.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Manufacturer Part Number	NSCSMNN150PDUNV
Package 4-SIP Module Series TruStability? NSC Pressure Type Differential Operating Pressure ±150 PSI (±1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 258.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series TruStability? NSC Pressure Type Differential Operating Pressure ±150 PSI (±1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 258.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeDifferentialOperating Pressure±150 PSI (±1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 258.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure±250 PSI (±1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP		Pressure Sensors, Transducers
Pressure TypeDifferentialOperating Pressure±150 PSI (±1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 258.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure±250 PSI (±1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP	Package	4-SIP Module
Operating Pressure ±150 PSI (±1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 258.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput0 mV ~ 258.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure±250 PSI (±1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP	Pressure Type	Differential
Output $0 \text{ mV} \sim 258.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size $-$ Port Style $No \text{ Port}$ Features $-$ Termination Style $PC \text{ Pin}$ Maximum Pressure $\pm 250 \text{ PSI} (\pm 1723.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4\text{-SIP} \text{ Module}$ Supplier Device Package 4-SIP	Operating Pressure	±150 PSI (±1034.21 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure $\pm 250 \text{ PSI } (\pm 1723.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package $4-\text{SIP}$	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	0 mV ~ 258.5 mV (5V)
Port Size - No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Accuracy	±0.25%
Port Style No Port Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Port Size	-
Termination Style PC Pin Maximum Pressure ±250 PSI (±1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Port Style	No Port
Maximum Pressure ± 250 PSI (± 1723.69 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package 4-SIP	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package 4-SIP	Maximum Pressure	±250 PSI (±1723.69 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	4-SIP
		Report errors?

NSCSMNN150PDUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSCSMNN150PDUNV Payment Methods





















NSCSMNN150PDUNV Shipping Methods













If you have any question about NSCSMNN150PDUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com