

## **NSCSNBN015PDUNV**

### **NSCSNBN015PDUNV Information**



For Reference Only

Part Number NSCSNBN015PDUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRES 15PSI DIFF 12V SIP

Package 4-SIP, Dual Ports, Same Side

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# NSCSNBN015PDUNV Specifications

Manufacturer Part NumberNSCSNBN015PDUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP, Dual Ports, Same SideSeriesTruStability? NSCPressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 155 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP		
CategorySensors, TransducersPackage4-SIP, Dual Ports, Same SideSeriesTruStability? NSCPressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 155 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Manufacturer Part Number	NSCSNBN015PDUNV
Package 4-SIP, Dual Ports, Same Side Series Trustability? NSC Pressure Type Differential Operating Pressure ±15 PSI (±103.42 kPa) Output Type Wheatstone Bridge Output (0 mV ~ 155 mV (5V)) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features - Termination Style PC Pin Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature +40°C ~ 85°C Package / Case 4-SIP, Dual Ports, Same Side Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         4-SIP, Dual Ports, Same Side           Series         TruStability? NSC           Pressure Type         Differential           Operating Pressure         ±15 PSI (±103.42 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 155 mV (5V)           Accuracy         ±0.25%           Voltage - Supply         1.5 V ~ 12 V           Port Size         Male - 0.19" (4.8mm) Tube, Dual           Port Style         Barbless           Features         -           Termination Style         PC Pin           Maximum Pressure         ±30 PSI (±206.84 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         4-SIP, Dual Ports, Same Side           Supplier Device Package         4-SIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 155 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP		Pressure Sensors, Transducers
Pressure TypeDifferentialOperating Pressure±15 PSI (±103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 155 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Package	4-SIP, Dual Ports, Same Side
Operating Pressure ±15 PSI (±103.42 kPa)  Output Type Wheatstone Bridge  Output 0 mV ~ 155 mV (5V)  Accuracy ±0.25%  Voltage - Supply 1.5 V ~ 12 V  Port Size Male - 0.19" (4.8mm) Tube, Dual  Port Style Barbless  Features -  Termination Style PC Pin  Maximum Pressure ±30 PSI (±206.84 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP, Dual Ports, Same Side  Supplier Device Package 4-SIP	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput0 mV ~ 155 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP, Dual Ports, Same SideSupplier Device Package4-SIP	Pressure Type	Differential
Output $0 \text{ mV} \sim 155 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.19$ " (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4\text{-SIP}$ , Dual Ports, Same SideSupplier Device Package $4\text{-SIP}$	Operating Pressure	±15 PSI (±103.42 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port SizeMale - $0.19$ " (4.8mm) Tube, DualPort StyleBarblessFeatures-Termination StylePC PinMaximum Pressure $\pm 30 \text{ PSI}$ ( $\pm 206.84 \text{ kPa}$ )Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP}$ , Dual Ports, Same SideSupplier Device Package $4-\text{SIP}$	Output Type	Wheatstone Bridge
Voltage - Supply  1.5 V ~ 12 V  Port Size  Male - 0.19" (4.8mm) Tube, Dual  Port Style  Barbless  Features  - Termination Style  PC Pin  Maximum Pressure  ±30 PSI (±206.84 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  4-SIP, Dual Ports, Same Side  Supplier Device Package	Output	$0 \text{ mV} \sim 155 \text{ mV} (5\text{V})$
Port Size Male - 0.19" (4.8mm) Tube, Dual  Port Style Barbless  Features -  Termination Style PC Pin  Maximum Pressure ±30 PSI (±206.84 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP, Dual Ports, Same Side  4-SIP	Accuracy	±0.25%
Port Style Barbless  Features -  Termination Style PC Pin  Maximum Pressure ±30 PSI (±206.84 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case 4-SIP, Dual Ports, Same Side  Supplier Device Package 4-SIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin   Maximum Pressure $\pm 30$ PSI ( $\pm 206.84$ kPa)   Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case	Port Size	Male - 0.19" (4.8mm) Tube, Dual
Termination StylePC PinMaximum Pressure $\pm 30$ PSI ( $\pm 206.84$ kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4\text{-SIP}$ , Dual Ports, Same SideSupplier Device Package $4\text{-SIP}$	Port Style	Barbless
Maximum Pressure $\pm 30$ PSI ( $\pm 206.84$ kPa)  Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4\text{-SIP}$ , Dual Ports, Same Side  Supplier Device Package $4\text{-SIP}$	Features	-
Operating Temperature  -40°C ~ 85°C  Package / Case  4-SIP, Dual Ports, Same Side  Supplier Device Package  4-SIP	Termination Style	PC Pin
Package / Case 4-SIP, Dual Ports, Same Side Supplier Device Package 4-SIP	Maximum Pressure	±30 PSI (±206.84 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP, Dual Ports, Same Side
Report errors?	Supplier Device Package	4-SIP
		Report errors?

### **NSCSNBN015PDUNV Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **NSCSNBN015PDUNV Payment Methods**



















## **NSCSNBN015PDUNV Shipping Methods**













If you have any question about NSCSNBN015PDUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com