

NSCSSNN150PAUNV

NSCSSNN150PAUNV Information

Part Number NSCSSNN150PAUNV

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 150PSI ABSO 12V SIP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSCSSNN150PAUNV Specifications

Manufacturer Part NumberNSCSSNN150PAUNVManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeriesTruStability? NSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 94.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP		
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series TruStability? NSC Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 94.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Manufacturer Part Number	NSCSSNN150PAUNV
Package 4-SIP Module Series TruStability? NSC Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 94.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series TruStability? NSC Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 94.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Category	Sensors, Transducers
SeriesTruStability? NSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 94.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 94.5 mV (5V)Accuracy±0.25%Voltage - Supply1.5 V ~ 12 VPort Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package4-SIP	Package	4-SIP Module
Operating Pressure 150 PSI (1034.21 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 94.5 mV (5V) Accuracy ±0.25% Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Series	TruStability? NSC
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 94.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package $4-\text{SIP}$	Pressure Type	Absolute
Output $0 \text{ mV} \sim 94.5 \text{ mV} (5\text{V})$ Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package $4-\text{SIP}$	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $1.5 \text{ V} \sim 12 \text{ V}$ Port Size-Port StyleNo PortFeatures-Termination StylePC PinMaximum Pressure $250 \text{ PSI } (1723.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package $4-\text{SIP}$	Output Type	Wheatstone Bridge
Voltage - Supply 1.5 V ~ 12 V Port Size - Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	$0 \text{ mV} \sim 94.5 \text{ mV} (5\text{V})$
Port Size - No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Accuracy	±0.25%
Port Style No Port Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Voltage - Supply	1.5 V ~ 12 V
Features - Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Port Size	-
Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Port Style	No Port
Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Features	-
Operating Temperature -40°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package 4-SIP	Termination Style	PC Pin
Package / Case 4-SIP Module Supplier Device Package 4-SIP	Maximum Pressure	250 PSI (1723.69 kPa)
Supplier Device Package 4-SIP	Operating Temperature	-40°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	4-SIP
		Report errors?

NSCSSNN150PAUNV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSCSSNN150PAUNV Payment Methods



















NSCSSNN150PAUNV Shipping Methods













If you have any question about NSCSSNN150PAUNV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com