



NSD20M36 Information

www.melsener.com

For Reference Only

Part Number NSD20M36 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE CRTRDGE 36A 415VAC CYLINDR**Package**Cylindrical, Blade Terminal (Alternating)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NSD20M36 Specifications

Manufacturer Part NumberNSD20M36ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Alternating)SeriesNSDFuse TypeCartridgeCurrent Rating36AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.689" Dia x 1.362" L (17.50mm x 34.60mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Alternating) Series NSD Fuse Type Cartridge Current Rating 36A Voltage Rating - AC 415V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - Class - C	Manufacturer Part Number	NSD20M36
Flectrical, Specialty Fuses Package Cylindrical, Blade Terminal (Alternating) Series NSD Fuse Type Cartridge Current Rating 36A Voltage Rating - AC Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension Electrical, Specialty Fuses Cartridge Cartridge Cartridge Affine Affine Cartridge Affine Affine Affine Cartridge Affine Affi	Manufacturer	Eaton
Package Cylindrical, Blade Terminal (Alternating) Series NSD Fuse Type Cartridge Current Rating 36A Voltage Rating - AC 415V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Category	Circuit Protection
SeriesNSDFuse TypeCartridgeCurrent Rating36AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCylindrical, Blade Terminal (Alternating)Size / Dimension0.689" Dia x 1.362" L (17.50mm x 34.60mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 36A Voltage Rating - AC 415V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge A15V Cartridge - Size / Dimension Cartridge A16B A A A A A A A A A A A A A A B A A A A	Package	Cylindrical, Blade Terminal (Alternating)
Current Rating Voltage Rating - AC 415V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 36A 415V 415V 415V - 4	Series	NSD
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 415V 415V 415V 415V 415V 415V 415V 415V Approvals - Class - Approvals - Class Cylindrical, Blade Terminal (Alternating)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class -	Current Rating	36A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension - Class - Class - Class - Class Cylindrical, Blade Terminal (Alternating) Control of the	Voltage Rating - AC	415V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Voltage Rating - DC	-
Features - Class - Approvals - Coperating Temperature - Seaking Capacity @ Rated Voltage 80kA Mounting Type Holder Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Response Time	-
Class - Approvals - Coperating Temperature - Sereaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Approvals	-
Mounting Type Holder Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Alternating) Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.689" Dia x 1.362" L (17.50mm x 34.60mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminal (Alternating)
Report errors?	Size / Dimension	0.689" Dia x 1.362" L (17.50mm x 34.60mm)
		Report errors?

NSD20M36 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NSD20M36 Payment Methods





















NSD20M36 Shipping Methods













If you have any question about NSD20M36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com