



NTS245SFT3G Information



For Reference Only

Part Number NTS245SFT3G
Manufacturer ON Semiconductor

Category Discrete Semiconductor Products
Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 45V 2A SOD123FL

Package SOD-123F

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NTS245SFT3G Specifications

Manufacturer Part NumberNTS245SFT3GManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsBackageSOD-123FSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If630mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr90μA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123FSupplier Device PackageSOD-123FLOperating Temperature - Junction-65°C ~ 150°CReport errors?	1 (182 lest 10 8 specifications	
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageSOD-123FSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If630mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr90μA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123FSupplier Device PackageSOD-123FLOperating Temperature - Junction-65°C ~ 150°C	Manufacturer Part Number	NTS245SFT3G
Package SOD-123F Series - Contact Schottky Voltage - DC Reverse (Vr) (Max) 45V Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If 630mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 90µA @ 45V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction - 65°C ~ 150°C	Manufacturer	ON Semiconductor
PackageSOD-123FSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)2AVoltage - Forward (Vf) (Max) @ If630mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr90μA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123FSupplier Device PackageSOD-123FLOperating Temperature - Junction-65°C ~ 150°C	Category	Discrete Semiconductor Products
Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 45V Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If 630mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 90μA @ 45V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C		Diodes - Rectifiers - Single
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 45V Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package Operating Temperature - Junction Schottky 45V Capacitance @ Applied Device Package SOD-123FL Operating Temperature - Junction Schottky 45V Capacitance @ Applied Device Package SOD-123FL Operating Temperature - Junction	Package	SOD-123F
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 2A Voltage - Forward (Vf) (Max) @ If 630mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 90µA @ 45V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package Operating Temperature - Junction 45V 2A 630mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - Surface Mount Surface Mount Fackage / Case SOD-123F Supplier Device Package Operating Temperature - Junction -65°C ~ 150°C	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 630mV @ 2A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package Operating Temperature - Junction 2A 630mV @ 2A 630mV @ 2A Fast Recovery =< 500ns, > 200mA (Io) - Supplier Suppl	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If630mV @ 2ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr90μA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123FSupplier Device PackageSOD-123FLOperating Temperature - Junction-65°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	45V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr90μA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123FSupplier Device PackageSOD-123FLOperating Temperature - Junction-65°C ~ 150°C	Current - Average Rectified (Io)	2A
Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 90μA @ 45V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	630mV @ 2A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction 90µA @ 45V	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C	Current - Reverse Leakage @ Vr	90μA @ 45V
Package / Case SOD-123F Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package SOD-123FL Operating Temperature - Junction -65°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -65°C ~ 150°C	Package / Case	SOD-123F
	Supplier Device Package	SOD-123FL
Report errors?	Operating Temperature - Junction	-65°C ~ 150°C
		Report errors?

NTS245SFT3G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NTS245SFT3G Payment Methods



















NTS245SFT3G Shipping Methods













If you have any question about NTS245SFT3G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com