



### **NVH1D1C0CP2S Information**



For Reference Only

Part Number NVH1D1C0CP2S

Manufacturer APEM Inc.
Category Switches

Navigation Switches, Joystick

**Description** SWITCH THMBSTK CASTLE 50MA 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **NVH1D1C0CP2S Specifications**

Manufacturer Part Number         NVHID1COCP2S           Manufacturer         APEM Inc.           Category         Switches           Package         -           Series         NV           Type         Thumbstick, 2 - Axis           Actuator Type         Castle           Switch Function         4-Way Directional           Functions, Extra         -           Output         Digital (Mechanical Switch)           Voltage - Supply         -           Current Rating         50mA (DC)           Voltage Rating - AC         -           Voltage Rating - DC         12V           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Connector           Operating Temperature         -40°C ~ 65°C           Panel Cutout Dimensions         Circular - 16.20mm Dia           Ingress Protection         IP69K - Dust Tight, Water Resistant, Waterproof           Features         -           Report errors?	*		
Category Switches Navigation Switches, Joystick  Package - Series NV  Type Thumbstick, 2 - Axis  Actuator Type Castle Switch Function 4-Way Directional  Functions, Extra - Output Digital (Mechanical Switch)  Voltage - Supply - Current Rating SomA (DC)  Voltage Rating - AC Voltage Rating - DC Contact Material - Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -40°C ~ 65°C Panel Cutout Dimensions Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof Features	Manufacturer Part Number	NVH1D1C0CP2S	
Package         -           Series         NV           Type         Thumbstick, 2 - Axis           Actuator Type         Castle           Switch Function         4-Way Directional           Functions, Extra         -           Output         Digital (Mechanical Switch)           Voltage - Supply         -           Current Rating         50mA (DC)           Voltage Rating - AC         -           Voltage Rating - DC         12V           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Connector           Operating Temperature         -40°C ~ 65°C           Panel Cutout Dimensions         Circular - 16.20mm Dia           Ingress Protection         IP69K - Dust Tight, Water Resistant, Waterproof           Features         -	Manufacturer	APEM Inc.	
Package         -           Series         NV           Type         Thumbstick, 2 - Axis           Actuator Type         Castle           Switch Function         4-Way Directional           Functions, Extra         -           Output         Digital (Mechanical Switch)           Voltage - Supply         -           Current Rating         50mA (DC)           Voltage Rating - AC         -           Voltage Rating - DC         12V           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Connector           Operating Temperature         -40°C ~ 65°C           Panel Cutout Dimensions         Circular - 16.20mm Dia           Ingress Protection         IP69K - Dust Tight, Water Resistant, Waterproof           Features         -	Category	Switches	
Series         NV           Type         Thumbstick, 2 - Axis           Actuator Type         Castle           Switch Function         4-Way Directional           Functions, Extra         -           Output         Digital (Mechanical Switch)           Voltage - Supply         -           Current Rating         50mA (DC)           Voltage Rating - AC         -           Voltage Rating - DC         12V           Contact Material         -           Contact Finish         -           Mounting Type         Panel Mount           Termination Style         Connector           Operating Temperature         -40°C ~ 65°C           Panel Cutout Dimensions         Circular - 16.20mm Dia           Ingress Protection         IP69K - Dust Tight, Water Resistant, Waterproof           Features         -		Navigation Switches, Joystick	
Type Castle  Switch Function 4-Way Directional  Functions, Extra -  Output Digital (Mechanical Switch)  Voltage - Supply -  Current Rating 50mA (DC)  Voltage Rating - AC -  Voltage Rating - DC 12V  Contact Material -  Contact Finish -  Mounting Type Panel Mount  Termination Style Connector  Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia  Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof  Features -  Castle  A-Way Directional  A-Way	Package	-	
Actuator Type Castle  Switch Function 4-Way Directional  Functions, Extra - Output Digital (Mechanical Switch)  Voltage - Supply - Current Rating 50mA (DC)  Voltage Rating - AC - Voltage Rating - DC 12V  Contact Material - Contact Finish - Mounting Type Panel Mount  Termination Style Connector Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof Features -	Series	NV	
Switch Function4-Way DirectionalFunctions, Extra-OutputDigital (Mechanical Switch)Voltage - Supply-Current Rating50mA (DC)Voltage Rating - AC-Voltage Rating - DC12VContact Material-Contact Finish-Mounting TypePanel MountTermination StyleConnectorOperating Temperature-40°C ~ 65°CPanel Cutout DimensionsCircular - 16.20mm DiaIngress ProtectionIP69K - Dust Tight, Water Resistant, WaterproofFeatures-	Туре	Thumbstick, 2 - Axis	
Functions, Extra  Output  Digital (Mechanical Switch)  Voltage - Supply  - Current Rating  50mA (DC)  Voltage Rating - AC  Voltage Rating - DC  12V  Contact Material  - Contact Finish  - Mounting Type  Panel Mount  Termination Style  Operating Temperature  -40°C ~ 65°C  Panel Cutout Dimensions  Ingress Protection  Features  -  Digital (Mechanical Switch)  -  Digital (Mechanical S	Actuator Type	Castle	
OutputDigital (Mechanical Switch)Voltage - Supply-Current Rating50mA (DC)Voltage Rating - AC-Voltage Rating - DC12VContact Material-Contact Finish-Mounting TypePanel MountTermination StyleConnectorOperating Temperature-40°C ~ 65°CPanel Cutout DimensionsCircular - 16.20mm DiaIngress ProtectionIP69K - Dust Tight, Water Resistant, WaterproofFeatures-	Switch Function	4-Way Directional	
Voltage - Supply Current Rating 50mA (DC)  Voltage Rating - AC - Voltage Rating - DC 12V  Contact Material - Contact Finish - Mounting Type Panel Mount  Termination Style Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia Ingress Protection Features	Functions, Extra	-	
Current Rating 50mA (DC)  Voltage Rating - AC -  Voltage Rating - DC 12V  Contact Material -  Contact Finish -  Mounting Type Panel Mount  Termination Style Connector  Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia  Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof  Features -  50mA (DC)  -  Connector  -  Contact Material -  -  Contact	Output	Digital (Mechanical Switch)	
Voltage Rating - AC  Voltage Rating - DC  12V  Contact Material  - Contact Finish  - Mounting Type  Panel Mount  Termination Style  Connector  Operating Temperature  -40°C ~ 65°C  Panel Cutout Dimensions  Circular - 16.20mm Dia  Ingress Protection  IP69K - Dust Tight, Water Resistant, Waterproof  Features  -  -  -  -  -  -  -  -  -  -  -  -  -	Voltage - Supply	-	
Voltage Rating - DC  Contact Material  Contact Finish  -  Mounting Type  Panel Mount  Termination Style  Connector  Operating Temperature  -40°C ~ 65°C  Panel Cutout Dimensions  Circular - 16.20mm Dia  Ingress Protection  IP69K - Dust Tight, Water Resistant, Waterproof  Features  -  12V  Contact Material  -  Contact Material  -  Contact Finish  -  Panel Mount  Connector  Connector  -40°C ~ 65°C  Panel Cutout Dimensions  Circular - 16.20mm Dia  IP69K - Dust Tight, Water Resistant, Waterproof  Features	Current Rating	50mA (DC)	
Contact Material - Contact Finish - Mounting Type Panel Mount  Termination Style Connector Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof Features -	Voltage Rating - AC	-	
Contact Finish  Mounting Type  Panel Mount  Termination Style  Connector  Operating Temperature  -40°C ~ 65°C  Panel Cutout Dimensions  Circular - 16.20mm Dia  Ingress Protection  IP69K - Dust Tight, Water Resistant, Waterproof  Features  -	Voltage Rating - DC	12V	
Mounting Type Panel Mount  Termination Style Connector  Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia  Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof  Features -	Contact Material	-	
Termination Style Connector  Operating Temperature $-40^{\circ}\text{C} \sim 65^{\circ}\text{C}$ Panel Cutout Dimensions Circular - 16.20mm Dia  Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof  Features -	Contact Finish	-	
Operating Temperature -40°C ~ 65°C  Panel Cutout Dimensions Circular - 16.20mm Dia  Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof  Features -	Mounting Type	Panel Mount	
Panel Cutout Dimensions Circular - 16.20mm Dia Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof Features -	Termination Style	Connector	
Ingress Protection IP69K - Dust Tight, Water Resistant, Waterproof Features -	Operating Temperature	-40°C ~ 65°C	
Features -	Panel Cutout Dimensions	Circular - 16.20mm Dia	
	Ingress Protection	IP69K - Dust Tight, Water Resistant, Waterproof	
Report errors?	Features	-	
			Report errors?

### **NVH1D1C0CP2S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **NVH1D1C0CP2S Payment Methods**



















### **NVH1D1C0CP2S Shipping Methods**













If you have any question about NVH1D1C0CP2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com