

# **OMI-SS-224L,500 Information**

Heisener.com

Part Number OMI-SS-224L,500

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 24V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **OMI-SS-224L,500 Specifications**

Manufacturer Part Number     OMI-SS-224L,500       Manufacturer     TE Connectivity Potter & Brumfield Relays       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     OMI, OEG       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     22.5mA       Coil Voltage     24VDC       Contact Form     DPDT (2 Form C)       Contact Rating (Current)     5A       Switching Voltage     250VAC, 30VDC - Max       Turn On Voltage (Max)     18 VDC       Turn Off Voltage (Min)     1.2 VDC       Operate Time     20ms       Release Time     8ms       Features     Sealed - Flux Protection       Mounting Type     Through Hole       Termination Style     PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	OMI-SS-224L,500
Package-SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         OMI, OEG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         22.5mA           Coil Voltage         24VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 30VDC - Max           Turn On Voltage (Max)         18 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         20ms           Release Time         8ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 22.5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	OMI, OEG
Coil Current22.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  5A  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Current	22.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  5A  Solve Annual Common Style  5A  Sealed - Max  Sealed - Max  Features  For Pin	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 8ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  8ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	18 VDC
Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **OMI-SS-224L,500 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **OMI-SS-224L,500 Payment Methods**



















### **OMI-SS-224L,500 Shipping Methods**













If you have any question about OMI-SS-224L,500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com