



Heisener.com

OMIT-SH-124LM,300 Information

OMIT-SH-124LM,300 Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OMIT-SH-124LM,300 Specifications

Manufacturer Part Number OMIT-SH-124LM,300 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series OMIT, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 22.5mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesOMIT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	OMIT-SH-124LM,300
Package-SeriesOMIT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesOMIT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesOMIT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 22.5mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	OMIT, OEG
Coil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage240VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	22.5mA
Contact Rating (Current) Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 240VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	240VAC, 30VDC - Max
Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Insulation - Class A, Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

OMIT-SH-124LM,300 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OMIT-SH-124LM,300 Payment Methods



















OMIT-SH-124LM,300 Shipping Methods













If you have any question about OMIT-SH-124LM,300, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com