

OP293FS Information



For Reference Only

Part Number OP293FS

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 35KHZ RRO 8SOIC **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OP293FS Specifications

Manufacturer Part Number OP293FS Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.015 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 250μV Current - Output / Channel 25mA Voltage - Supply, Single/Dual (±) 1.7 V ~ 36 V, ±0.85 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Surplier Device Package 8-SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.015 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 250µV Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	OP293FS
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package	Manufacturer	Analog Devices Inc.
Package8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output TypeRail-to-RailSlew Rate0.015 V/μsGain Bandwidth Product35kHz-3db Bandwidth-Current - Input Bias20nAVoltage - Input Offset250μVCurrent - Supply30μACurrent - Output / Channel25mAVoltage - Supply, Single/Dual (±)1.7 V ~ 36 V, ±0.85 V ~ 18 VOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.015 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 250μV Current - Supply 30μA Current - Output / Channel 25mA Voltage - Supply, Single/Dual (±) 1.7 V ~ 36 V, ±0.85 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 0.015 V/ μ s Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 250 μ V Current - Supply 30 μ A Current - Output / Channel 25mA Voltage - Supply, Single/Dual (\pm) 1.7 V ~ 36 V, \pm 0.85 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Package	8-SOIC (0.154", 3.90mm Width)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Series	-
Output Type Rail-to-Rail Slew Rate 0.015 V/ μ s Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset 250 μ V Current - Supply 30 μ A Current - Output / Channel 25mA Voltage - Supply, Single/Dual (\pm) 1.7 V ~ 36 V, \pm 0.85 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Amplifier Type	General Purpose
Slew Rate $0.015 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 20nA Voltage - Input Offset $250\mu\text{V}$ Current - Supply $30\mu\text{A}$ Current - Output / Channel 25mA Voltage - Supply, Single/Dual (\pm) $1.7 \text{ V} \sim 36 \text{ V}, \pm 0.85 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case $8\text{-SOIC }(0.154^{\circ}\text{H}, 3.90\text{mm Width})$	Number of Circuits	2
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Output Type	Rail-to-Rail
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Slew Rate	0.015 V/μs
Current - Input Bias $20nA$ Voltage - Input Offset $250\mu V$ Current - Supply $30\mu A$ Current - Output / Channel $25mA$ Voltage - Supply, Single/Dual (\pm) $1.7\ V \sim 36\ V, \pm 0.85\ V \sim 18\ V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Surface Mount $-40^{\circ}C \sim 125^{\circ}C \sim 125^{\circ}C \sim 125^{\circ}C$	Gain Bandwidth Product	35kHz
Voltage - Input Offset	-3db Bandwidth	-
Current - Supply $30\mu A$ Current - Output / Channel $25mA$ Voltage - Supply, Single/Dual (\pm) $1.7 \text{ V} \sim 36 \text{ V}, \pm 0.85 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Surface Mount $8-\text{SOIC}$ (0.154", 3.90mm Width)	Current - Input Bias	20nA
Current - Output / Channel 25mA Voltage - Supply, Single/Dual (±) $1.7 \text{ V} \sim 36 \text{ V}, \pm 0.85 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $8\text{-SOIC } (0.154^{\circ}\text{H}, 3.90\text{mm Width})$	Voltage - Input Offset	250μV
Voltage - Supply, Single/Dual (\pm) 1.7 V ~ 36 V, \pm 0.85 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Supply	30μΑ
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Current - Output / Channel	25mA
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)	Voltage - Supply, Single/Dual (±)	1.7 V ~ 36 V, ±0.85 V ~ 18 V
Package / Case 8-SOIC (0.154", 3.90mm Width)	Operating Temperature	-40°C ~ 125°C
	Mounting Type	Surface Mount
Supplier Device Package 8-SOIC	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplied Device I dekage 0 501C	Supplier Device Package	8-SOIC
Report error		Report errors?

OP293FS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OP293FS Payment Methods



















OP293FS Shipping Methods













If you have any question about OP293FS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com