



OP484FPZ Information

For Reference Only

Part Number OP484FPZ

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 4.25MHZ RRO 14DIP

Package 14-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OP484FPZ Specifications

Manufacturer Part Number OP484FPZ Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 V/µs Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250µV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP (D.300", 7.62mm)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 V/μs Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250μV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Manufacturer Part Number	OP484FPZ
PackageLinear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage 14 -DIP $(0.300", 7.62mm)$ Series-Amplifier TypeGeneral PurposeNumber of Circuits 4 Output TypeRail-to-RailSlew Rate $4 \text{V/}\mu\text{s}$ Gain Bandwidth Product 4.25MHz -3db Bandwidth-Current - Input Bias 80nA Voltage - Input Offset $250\mu\text{V}$ Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 36 \text{ V}, \pm 1.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting TypeThrough HolePackage / Case 14 -DIP $(0.300", 7.62mm)$ Supplier Device Package 14 -PDIP	Manufacturer	Analog Devices Inc.
Package 14-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 V/µs Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250µV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 V/μs Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250μV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 V/μs Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250μV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Package	14-DIP (0.300", 7.62mm)
Number of Circuits 4 Output Type Rail-to-Rail Slew Rate 4 $V/\mu s$ Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250 μV Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) 3 $V \sim 36 V$, $\pm 1.5 V \sim 18 V$ Operating Temperature -40°C ~ 125 °C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Series	-
Output Type Rail-to-Rail Slew Rate $4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset $250\mu\text{V}$ Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 36 \text{ V}, \pm 1.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Amplifier Type	General Purpose
Slew Rate $4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset $250\mu\text{V}$ Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 36 \text{ V}, \pm 1.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Number of Circuits	4
Gain Bandwidth Product 4.25MHz -3db Bandwidth - Current - Input Bias 80nA Voltage - Input Offset 250 μ V Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 36 V, \pm 1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Output Type	Rail-to-Rail
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Slew Rate	4 V/μs
Current - Input Bias 80nA Voltage - Input Offset 250 μ V Current - Supply 2.25mA Current - Output / Channel 10mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 36 V, \pm 1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Gain Bandwidth Product	4.25MHz
Voltage - Input Offset $250\mu V$ Current - Supply $2.25mA$ Current - Output / Channel $10mA$ Voltage - Supply, Single/Dual (\pm) $3 V \sim 36 V$, $\pm 1.5 V \sim 18 V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Through Hole Package / Case 14 -DIP $(0.300^{\circ}, 7.62mm)$ Supplier Device Package	-3db Bandwidth	-
Current - Supply Current - Output / Channel 10mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package	Current - Input Bias	80nA
Current - Output / Channel $10mA$ Voltage - Supply, Single/Dual (\pm) $3 \text{ V} \sim 36 \text{ V}, \pm 1.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Through Hole Package / Case 14-DIP (0.300° , $7.62mm$) Supplier Device Package 14-PDIP	Voltage - Input Offset	250μV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 36 V, \pm 1.5 V ~ 18 V Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Current - Supply	2.25mA
Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Current - Output / Channel	10mA
Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Voltage - Supply, Single/Dual (±)	3 V ~ 36 V, ±1.5 V ~ 18 V
Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-PDIP	Operating Temperature	-40°C ~ 125°C
Supplier Device Package 14-PDIP	Mounting Type	Through Hole
	Package / Case	14-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	14-PDIP
		Report errors?

OP484FPZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OP484FPZ Payment Methods



















OP484FPZ Shipping Methods













If you have any question about OP484FPZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com