



OPA241PA Information



For Reference Only

Part Number OPA241PA

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 35KHZ RRO 8DIP

Package 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OPA241PA Specifications

Manufacturer Part Number OPA241PA Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100μV Current - Output / Offset 100μV Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) 2.7 V ~ 36 V, ±1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-DIP (0.300", 7.62mm)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100μV Current - Supply 27μA Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) 2.7 V ~ 36 V, ±1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Manufacturer Part Number	OPA241PA
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100μV Current - Supply 27μA Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) 2.7 V ~ 36 V, ±1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Manufacturer	Texas Instruments
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/μs Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100μV Current - Supply 27μA Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) 2.7 V ~ 36 V, ±1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Category	Integrated Circuits (ICs)
Series-Amplifier TypeGeneral PurposeNumber of Circuits1Output TypeRail-to-RailSlew Rate0.01 V/μsGain Bandwidth Product35kHz-3db Bandwidth-Current - Input Bias4nAVoltage - Input Offset100μVCurrent - Supply27μACurrent - Output / Channel21mAVoltage - Supply, Single/Dual (±)2.7 V ~ 36 V, ±1.35 V ~ 18 VOperating Temperature-40°C ~ 85°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/ μ s Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100 μ V Current - Supply 27 μ A Current - Output / Channel 21mA Voltage - Supply, Single/Dual (\pm) 2.7 V ~ 36 V, \pm 1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 1 Output Type Rail-to-Rail Slew Rate 0.01 V/ μ s Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100 μ V Current - Supply 27 μ A Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) 2.7 V ~ 36 V, ±1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Series	-
Output Type Rail-to-Rail Slew Rate 0.01 V/ μ s Gain Bandwidth Product 35kHz -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100 μ V Current - Supply 27 μ A Current - Output / Channel 21mA Voltage - Supply, Single/Dual (\pm) 2.7 V ~ 36 V, \pm 1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Amplifier Type	General Purpose
Slew Rate 0.01 V/ μ s 35kHz -3db Bandwidth Product 35kHz - -3db Bandwidth - Current - Input Bias 4nA Voltage - Input Offset 100 μ V Current - Supply 27 μ A Current - Output / Channel 21mA Voltage - Supply, Single/Dual (\pm) 2.7 V ~ 36 V, \pm 1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Number of Circuits	1
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Output Type	Rail-to-Rail
$-3db \ Bandwidth \\ Current - Input \ Bias \\ Voltage - Input \ Offset \\ 100\mu V \\ Current - Supply \\ 27\mu A \\ Current - Output / Channel \\ Voltage - Supply, Single/Dual (\pm) 2.7 \ V \sim 36 \ V, \pm 1.35 \ V \sim 18 \ V \\ Operating \ Temperature \\ Mounting \ Type \\ Through \ Hole \\ Package / Case \\ 8-DIP (0.300'', 7.62mm) \\ Supplier \ Device \ Package \\ 8-PDIP$	Slew Rate	0.01 V/μs
Current - Input Bias $4nA$ Voltage - Input Offset $100\mu V$ Current - Supply $27\mu A$ Current - Output / Channel $21mA$ Voltage - Supply, Single/Dual (±) $2.7 \ V \sim 36 \ V, \pm 1.35 \ V \sim 18 \ V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Through Hole Package / Case 8 -DIP $(0.300^{\circ}, 7.62mm)$ Supplier Device Package 8 -PDIP	Gain Bandwidth Product	35kHz
Voltage - Input Offset	-3db Bandwidth	-
Current - Supply $27\mu A$ Current - Output / Channel $21mA$ Voltage - Supply, Single/Dual (±) $2.7 \text{ V} \sim 36 \text{ V}, \pm 1.35 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Through Hole Package / Case $8\text{-DIP} (0.300^{\circ}, 7.62mm)$ Supplier Device Package 8-PDIP	Current - Input Bias	4nA
Current - Output / Channel 21mA Voltage - Supply, Single/Dual (±) $2.7 \text{ V} \sim 36 \text{ V}, \pm 1.35 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeThrough HolePackage / Case $8\text{-DIP} (0.300^{\circ}, 7.62 \text{mm})$ Supplier Device Package 8-PDIP	Voltage - Input Offset	$100\mu V$
Voltage - Supply, Single/Dual (\pm) 2.7 V ~ 36 V, \pm 1.35 V ~ 18 V Operating Temperature -40°C ~ 85°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Current - Supply	27μΑ
$ \begin{array}{lll} \mbox{Operating Temperature} & -40^{\circ}\mbox{C} \sim 85^{\circ}\mbox{C} \\ \mbox{Mounting Type} & \mbox{Through Hole} \\ \mbox{Package / Case} & 8-\mbox{DIP } (0.300", 7.62\mbox{mm}) \\ \mbox{Supplier Device Package} & 8-\mbox{PDIP} \\ \end{array} $	Current - Output / Channel	21mA
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Voltage - Supply, Single/Dual (±)	2.7 V ~ 36 V, ±1.35 V ~ 18 V
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 8-PDIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-PDIP
report errors.		Report errors?

OPA241PA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OPA241PA Payment Methods



















OPA241PA Shipping Methods













If you have any question about OPA241PA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com