

ORWH-SH-124DM1F,000

ORWH-SH-124DM1F,000 Information



For Reference Only

Part Number ORWH-SH-124DM1F,000

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ORWH-SH-124DM1F,000 Specifications

Manufacturer Part Number ORWH-SH-124DM1F,000 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series ORWH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole		
Category Relays Power Relays, Over 2 Amps Package - Series ORWH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Manufacturer Part Number	ORWH-SH-124DM1F,000
Package - Series ORWH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - GRWH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Category	Relays
Series ORWH, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage277VAC, 28VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Fully	Package	-
Coil Type Non Latching Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Series	ORWH, OEG
Coil Current 15mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Coil Current	15mA
Contact Rating (Current) Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Coil Voltage	24VDC
Switching Voltage 277VAC, 28VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Contact Rating (Current)	10A
Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Fully	Switching Voltage	277VAC, 28VDC - Max
Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Fully	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Insulation - Class F, Sealed - Fully	Turn Off Voltage (Min)	2.4 VDC
Features Insulation - Class F, Sealed - Fully	Operate Time	10ms
·	Release Time	5ms
Mounting Type Through Hole	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

ORWH-SH-124DM1F,000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ORWH-SH-124DM1F,000 Payment Methods



















ORWH-SH-124DM1F,000 Shipping Methods













If you have any question about ORWH-SH-124DM1F,000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com