



OSZ-SH-124DM8,000 Information

Heisener.com

OSZ-SH-124DM8,000 Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OSZ-SH-124DM8,000 Specifications

Manufacturer Part Number OSZ-SH-124DM8,000 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series OSZ, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 22.5mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesOSZ, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	OSZ-SH-124DM8,000
Package-SeriesOSZ, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesOSZ, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesOSZ, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 22.5mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	OSZ, OEG
Coil Current22.5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	22.5mA
Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 24VDC - Max
Operate Time20msRelease Time10msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class A, Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

OSZ-SH-124DM8,000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OSZ-SH-124DM8,000 Payment Methods



















OSZ-SH-124DM8,000 Shipping Methods













If you have any question about OSZ-SH-124DM8,000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com