

OUAZ-SH-106L,900 Information



For Reference Only

Part Number OUAZ-SH-106L,900

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM SPDT 1A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OUAZ-SH-106L,900 Specifications

| Manufacturer Part Number OUAZ-SH-106L,900 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series OUAZ, OEG Relay Type Telecom Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | | |
|--|--------------------------|---|
| CategoryRelaysPackage-SeriesOUAZ, OEGRelay TypeTelecomCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage120VAC, 24VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time7msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | OUAZ-SH-106L,900 |
| Package-SeriesOUAZ, OEGRelay TypeTelecomCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage120VAC, 24VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time7msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer | TE Connectivity Potter & Brumfield Relays |
| Package - Series OUAZ, OEG Relay Type Telecom Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Category | Relays |
| SeriesOUAZ, OEGRelay TypeTelecomCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage120VAC, 24VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time7msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | | Signal Relays, Up to 2 Amps |
| Relay TypeTelecomCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage120VAC, 24VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time7msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Series | OUAZ, OEG |
| Coil Current Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style 9C Pin | Relay Type | Telecom |
| Coil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage120VAC, 24VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time7msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Coil Type | Non Latching |
| Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style | Coil Current | 33.3mA |
| Contact Rating (Current) Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style | Coil Voltage | 6VDC |
| Switching Voltage 120VAC, 24VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Contact Form | SPDT (1 Form C) |
| Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Contact Rating (Current) | 1A |
| Turn Off Voltage (Min) Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Switching Voltage | 120VAC, 24VDC - Max |
| Operate Time 10ms Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn On Voltage (Max) | 4.5 VDC |
| Release Time 7ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 0.6 VDC |
| Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Operate Time | 10ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 7ms |
| Termination Style PC Pin | Features | Sealed - Fully |
| • | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

OUAZ-SH-106L,900 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OUAZ-SH-106L,900 Payment Methods



















OUAZ-SH-106L,900 Shipping Methods













If you have any question about OUAZ-SH-106L,900, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com