



OZT-SH-112LM1,294 Information

Heisener.com

Part Number OZT-SH-112LM1,294

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 8A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OZT-SH-112LM1,294 Specifications

Manufacturer Part NumberOZT-SH-112LM1,294ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesOZT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage240VAC, 24VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesOZT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage240VAC, 24VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	OZT-SH-112LM1,294
Package - OZT, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style POZT, OEG General Purpose General Purpose (A. 4.4mA A. 4.4mA A. 4.4mA A. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesOZT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage240VAC, 24VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesOZT, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage240VAC, 24VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage240VAC, 24VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time8msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 44.4mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	OZT, OEG
Coil Current 44.4mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	44.4mA
Contact Rating (Current) Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	12VDC
Switching Voltage 240VAC, 24VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Urn Off Voltage (Min) 9 VDC 0.6 VDC Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	240VAC, 24VDC - Max
Operate Time 20ms Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 8ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Insulation - Class A, Sealed - Fully
•	Mounting Type	Through Hole
D	Termination Style	PC Pin
Report errors?		Report errors?

OZT-SH-112LM1,294 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OZT-SH-112LM1,294 Payment Methods



















OZT-SH-112LM1,294 Shipping Methods













If you have any question about OZT-SH-112LM1,294, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com