



P2012B/CUL Information

Heisener.com

For Reference Only

Part Number P2012B/CUL
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 10A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P2012B/CUL Specifications

Manufacturer Part Number P2012B/CUL Manufacturer NKK Switches Category Switches Package - Toggle Switches Series P Circuit SPDT Switch Function On-On Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -		
Category Switches Package - Series P Circuit SPDT Switch Function On-On Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Manufacturer Part Number	P2012B/CUL
Package - Series P Circuit SPDT Switch Function On-On Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Manufacturer	NKK Switches
Package - Series P Circuit SPDT Switch Function On-On Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Category	Switches
SeriesPCircuitSPDTSwitch FunctionOn-OnCurrent Rating10A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating10A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Package	-
Switch Function Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features On-On On On-On On O	Series	P
Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC Standard Round Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round 17.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V Name Actuator Length - Carnal Round Non-Illuminated 17.50mm Non-Illuminated Non-Illuminated Non-Illuminated Solder Lug Panel Mount Circular - 12.50mm Dia M12 x 1 Ingress Protection - Carnal Round - Carnal Round Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated - Carnal Round Non-Illuminated Non-Illuminated Non-Illuminated Non-Illuminated Non-Illuminated - Carnal Round -	Switch Function	On-On
Voltage Rating - DC-Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Current Rating	10A (AC)
Actuator Type Standard Round 17.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Voltage Rating - AC	125V
Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread Ingress Protection Features - 17.50mm Concluded - Read Mount Circular - 12.50mm Dia M12 x 1 Ingress Protection - Features	Voltage Rating - DC	-
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Actuator Length	17.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 12.50mm Dia M12 x 1 - - -	Mounting Type	Panel Mount
Bushing Thread M12 x 1 Ingress Protection - Features -	Termination Style	Solder Lug
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features -	Bushing Thread	M12 x 1
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

P2012B/CUL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P2012B/CUL Payment Methods





















P2012B/CUL Shipping Methods













If you have any question about P2012B/CUL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com