



P40C43A12C1-120 Information

Heisener.com

Part Number P40C43A12C1-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY CONTACTOR DPST 40A 120V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P40C43A12C1-120 Specifications

Manufacturer Part Number P40C43A12C1-120 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Package - Series P40 Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)		
Category Relays Power Relays, Over 2 Amps Package - Series P40 Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	P40C43A12C1-120
Package - Series P40 Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series P40 Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series P40 Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Sorew Terminal, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage120VACContact FormDPST-NO(DM), SPST-NC(DB)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleScrew Terminal, Quick Connect - 0.250" (6.3mm)	Series	P40
Coil Current Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features - Mounting Type Chassis Mount Termination Style - Screw Terminal, Quick Connect - 0.250" (6.3mm)	Relay Type	Contactor
Coil Voltage 120VAC Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Server Terminal, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form DPST-NO(DM), SPST-NC(DB) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Coil Current	-
Contact Rating (Current) Switching Voltage 600VAC - Max 102 VAC Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time Release Time - Release Time - Mounting Type Chassis Mount Termination Style 40A 40A 40A 40A 600VAC - Max 102 VAC 102 VAC - Chassis Mount Screw Terminal, Quick Connect - 0.250" (6.3mm)	Coil Voltage	120VAC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Contact Form	DPST-NO(DM), SPST-NC(DB)
Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time Release Time - Release Time - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	40A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Chassis Mount Termination Style Crew Terminal, Quick Connect - 0.250" (6.3mm)	Switching Voltage	600VAC - Max
Operate Time - CRelease Time - CRelease Time - CRelease Time - CRelease Time - CRestures - CRestures CRESTURE CRES	Turn On Voltage (Max)	102 VAC
Release Time - Features - Mounting Type Chassis Mount Screw Terminal, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features - Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Features	-
•	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal, Quick Connect - 0.250" (6.3mm)
		Report errors?

P40C43A12C1-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P40C43A12C1-120 Payment Methods



















P40C43A12C1-120 Shipping Methods













If you have any question about P40C43A12C1-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com