



P41C47DHO103Z03 Information

Heisener.com

Part Number P41C47DHO103Z03

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY CONTACTOR 4PST 25A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P41C47DHO103Z03 Specifications

Manufacturer Part Number P41C47DH0103Z03 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series P41 Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm) Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series P41 Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	P41C47DHO103Z03
Package - Series P41 Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series P41 Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
Series P41 Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type Contactor Coil Type Non Latching Coil Current 286mA Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current286mACoil Voltage24VDCContact Form4PST-NO-DM (4 Form X)Contact Rating (Current)25ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Series	P41
Coil Current286mACoil Voltage24VDCContact Form4PST-NO-DM (4 Form X)Contact Rating (Current)25ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Relay Type	Contactor
Coil Voltage 24VDC Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form 4PST-NO-DM (4 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Current	286mA
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 25A 600VAC - Max 18 VDC - Insulation - Class B Chassis Mount Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VDC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	4PST-NO-DM (4 Form X)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	25A
Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Switching Voltage	600VAC - Max
Operate Time	Turn On Voltage (Max)	18 VDC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

P41C47DHO103Z03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P41C47DHO103Z03 Payment Methods



















P41C47DHO103Z03 Shipping Methods













If you have any question about P41C47DHO103Z03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com