

P4SMA10CA M2G

P4SMA10CA M2G Information

Heisener.com	 P4SMA10CA M2G TSC America Inc. Circuit Protection TVS - Diodes DIODE, TVS, BIDIRECTIONAL, 400W, DO-214AC, SMA For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



P4SMA10CA M2G Specifications

Manufacturer Part NumberP4SMA10CA M2GManufacturerTSC America Inc.CategoryCircuit ProtectionTVS - DiodesTVS - DiodesPackageDo-214AC, SMASeriesPackageTypeZenerUnidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 150°C (TJ)Monting TypeSou CaltAC, SMAPackage / CaseDo-214AC, SMA	
CategoryCircuit ProtectionPackageTVS - DiodesPackageDo-214AC, SMASeriesP4SMATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VPower - Peak Pulse (10/1000µs)90WPower Line ProtectionMouApplicationsGeneral PurposeApplications55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseSurface Mount	
TVS - Diodes Package TVS - Diodes Package DO-214AC, SMA Series P4SMA Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 8.55V Voltage - Breakdown (Min) 9.5V Voltage - Clamping (Max) @ Ipp 14.5V Power Line Protection Aou Power Line Protection General Purpose Capacitance @ Frequency - Operating Temperature S5°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA	
PackageDO-214AC, SMASeriesP4SMATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower Line ProtectionMouApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 150°C (TJ)Mounting TypeSurface MouPackage / CaseDO-214AC, SMA	
SeriesP4SMATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse (10/1000µs)MouPower Line ProtectionKoApplicationsGeneral PurposeCapacitance @ Frequency-Operating TemperatureStrice MountMounting TypeSurface MountPackage / CaseDO-214AC, SMA	
TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse (10/1000µs)MouPower Line ProtectionKoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 150°C (TJ)Mouting TypeSurface MountPackage / CaseDO-214AC, SMA	
Unidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse (10/1000µs)400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Bidirectional Channels1Bidirectional Channels1Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse (10/1000µs)400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Voltage - Reverse Standoff (Typ)8.55VVoltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDo-214AC, SMA	
Voltage - Breakdown (Min)9.5VVoltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse (10/1000µs)400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Voltage - Clamping (Max) @ Ipp14.5VCurrent - Peak Pulse (10/1000µs)29APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Current - Peak Pulse (10/1000µs)29APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Power - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Capacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Mounting TypeSurface MountPackage / CaseDO-214AC, SMA	
Package / Case DO-214AC, SMA	
-	
Sound in Device Device and (CMA)	
Supplier Device Package DO-214AC (SMA)	
Rep	Report errors?

P4SMA10CA M2G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

P4SMA10CA M2G Payment Methods



P4SMA10CA M2G Shipping Methods



If you have any question about P4SMA10CA M2G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com