



P4SMA51A M2G Information

Heisener.com

For Reference Only

Part Number P4SMA51A M2G
Manufacturer TSC America Inc.
Category Circuit Protection
TVS - Diodes

Description DIODE, TVS, UNIDIRECTIONAL, 400W

Package DO-214AC, SMA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P4SMA51A M2G Specifications

Manufacturer TSC America Inc. Category Circuit Protection TVS - Diodes Package DO-214AC, SMA Series P4SMA Type Zener Unidirectional Channels - Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA	_	
Category Circuit Protection TVS - Diodes Package DO-214AC, SMA Series P4SMA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Manufacturer Part Number	P4SMA51A M2G
TVS - Diodes Package DO-214AC, SMA Series P4SMA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000μs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Manufacturer	TSC America Inc.
PackageDO-214AC, SMASeriesP4SMATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)43.6VVoltage - Breakdown (Min)48.5VVoltage - Clamping (Max) @ Ipp70.1VCurrent - Peak Pulse (10/1000μs)6APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)	Category	Circuit Protection
Series P4SMA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package		TVS - Diodes
Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Package	DO-214AC, SMA
Unidirectional Channels Bidirectional Channels Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp Current - Peak Pulse (10/1000µs) Fower - Peak Pulse Vower - Peak Pulse Rower - Peak Pulse General Purpose Capacitance @ Frequency Operating Temperature Package / Case Supplier Device Package DO-214AC (SMA)	Series	P4SMA
Bidirectional Channels Voltage - Reverse Standoff (Typ) 43.6V Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Туре	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 48.5V Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000μs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Unidirectional Channels	1
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000μs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp 70.1V Current - Peak Pulse (10/1000µs) 6A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Voltage - Reverse Standoff (Typ)	43.6V
Current - Peak Pulse (10/1000μs)6APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)	Voltage - Breakdown (Min)	48.5V
Power - Peak Pulse 400W Power Line Protection No Applications Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Voltage - Clamping (Max) @ Ipp	70.1V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Current - Peak Pulse (10/1000µs)	6A
Applications Capacitance @ Frequency Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Power - Peak Pulse	400W
Capacitance @ Frequency - Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Power Line Protection	No
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Applications	General Purpose
Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Capacitance @ Frequency	-
Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package DO-214AC (SMA)	Mounting Type	Surface Mount
	Package / Case	DO-214AC, SMA
Report errors?	Supplier Device Package	DO-214AC (SMA)
		Report errors?

P4SMA51A M2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P4SMA51A M2G Payment Methods



















P4SMA51A M2G Shipping Methods













If you have any question about P4SMA51A M2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com