



Heisener.com

#### P51-100-A-AF-I12-5V-000-000 Information

Part Number P51-100-A-AF-I12-5V-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

**Description** SENS 100PSI 5/8" 9/16-18 UNF 5V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **P51-100-A-AF-I12-5V-000-000 Specifications**

| Manufacturer Part NumberP51-100-A-AF-112-5V-000-000ManufacturerSSI Technologies IncCategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 9/16" (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'  |
|--|
| Category Sensors, Transducers  Package Cylinder Series MediaSensor?  Pressure Type Absolute Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply Port Size Male - 9/16" (14.29mm) UNF Port Style Features Amplified Output, Temperature Compensated   |
| Package Cylinder  Series MediaSensor?  Pressure Type Absolute  Operating Pressure  Output Type Analog Voltage  Output  1 V ~ 5 V  Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size Male - 9/16" (14.29mm) UNF  Port Style  Features MediaSensor, Transducers  MediaSensor, Transducers  MediaSensor, Transducers  MediaSensor, Transducers  1 V ~ 5 V  Absolute  1 00 PSI (689.48 kPa)  1 V ~ 5 V  4 Nalog Voltage  4 U ~ 5 V  4 Ccuracy  4 U ~ 5 V  Threaded  Threaded  Amplified Output, Temperature Compensated |
| PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 9/16" (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated  |
| SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 9/16" (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated   |
| Pressure Type  Absolute  Operating Pressure  100 PSI (689.48 kPa)  Output Type  Analog Voltage  Output  1 V ~ 5 V  Accuracy  ±0.5%  Voltage - Supply  8 V ~ 30 V  Port Size  Male - 9/16" (14.29mm) UNF  Port Style  Features  Amplified Output, Temperature Compensated   |
| Operating Pressure $100 \text{ PSI } (689.48 \text{ kPa})$ Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $9/16$ " (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated  |
| Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $9/16$ " (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated   |
| Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $9/16$ " (14.29mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated  |
| Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 9/16" (14.29 \text{mm}) \text{ UNF}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$  |
| Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 9/16'' (14.29 \text{mm}) \text{ UNF}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$  |
| Port Size Male - 9/16" (14.29mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  |
| Port Style Threaded Features Amplified Output, Temperature Compensated   |
| Features Amplified Output, Temperature Compensated   |
|  |
| Termination Style Cable 1'   |
|  |
| Maximum Pressure -   |
| Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$   |
| Package / Case Cylinder  |
| Supplier Device Package -  |
| Report errors?   |

#### P51-100-A-AF-I12-5V-000-000 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-100-A-AF-I12-5V-000-000 Payment Methods



















### P51-100-A-AF-I12-5V-000-000 Shipping Methods













If you have any question about P51-100-A-AF-I12-5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com