



Heisener.com

P51-15-A-U-MD-5V-000-000 Information

Part Number P51-15-A-U-MD-5V-000-000

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 15PSI 7/16-20-2B 1-5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-15-A-U-MD-5V-000-000 Specifications

Manufacturer Part Number P51-15-A-U-MD-5V-000-000 Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -			
Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure Operating Temperature - 40°C ~ 105°C Package / Case Supplice Device Package Sensors, Transducers Pressure Sensors, Transducers Rediacres 1 V ~ 5 V Accuracy Absolute Alsolutate Analog Voltage Analog Volt	Manufacturer Part Number	P51-15-A-U-MD-5V-000-000	
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Voltage Output Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package Cylinder Cylinder Cylinder Absolute Cylinder Absolute Analog Voltage Analog V	Manufacturer	SSI Technologies Inc	
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeFemale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers	
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeFemale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder	
Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - 15 PSI (103.42 kPa) Analog Voltage 1 V ~ 5 V Analog Voltage ### ### ### ### ### ### ### ### ### #	Series	MediaSensor?	
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 1\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Pressure Type	Absolute	
Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 1\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	15 PSI (103.42 kPa)	
Accuracy $\pm 1\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Output Type	Analog Voltage	
Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output	1 V ~ 5 V	
Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±1%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	Female - 7/16" (11.11mm) UNF	
Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case Cylinder Supplier Device Package -	Port Style	Threaded	
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Termination Style	MD, 4 Pin	
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-	
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C	
	Package / Case	Cylinder	
Report errors?	Supplier Device Package	-	
		Report errors	s?

P51-15-A-U-MD-5V-000-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-15-A-U-MD-5V-000-000 Payment Methods



















P51-15-A-U-MD-5V-000-000 Shipping Methods













If you have any question about P51-15-A-U-MD-5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com