

Heisener.com

# P51-15-S-L-I12-20MA-000-000

### P51-15-S-L-I12-20MA-000-000 Information

Part Number P51-15-S-L-I12-20MA-000-000

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 15PSIS M10 4-20 MA

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# P51-15-S-L-I12-20MA-000-000 Specifications

Manufacturer Part Number         P51-15-S-L-112-20MA-000-000           Manufacturer         SSI Technologies Inc           Category         Sensors, Transducers           Package         Cylinder           Series         MediaSensor?           Pressure Type         Sealed Gauge           Operating Pressure         15 PSI (103.42 kPa)           Output Type         Analog Current           Output         4 mA ~ 20 mA           Accuracy         ±1%           Voltage - Supply         8 V ~ 30 V           Port Size         Female - M10 x 1.25           Port Style         Threaded           Features         Amplified Output, Temperature Compensated           Termination Style         Cable 1'           Maximum Pressure         -           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -    Report errors?		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-15-S-L-I12-20MA-000-000
Package Cylinder  Series MediaSensor?  Pressure Type Sealed Gauge  Operating Pressure  Output Type Analog Current  Output 4 mA ~ 20 mA  Accuracy ±1%  Voltage - Supply 8 V ~ 30 V  Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Cable 1'  Maximum Pressure  Operating Temperature -40°C ~ 105°C  Package / Case  Supplier Device Package	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package  15 PSI (103.42 kPa) Analog Current Amalog Current -4mA ~ 20 mA -4mA -4mA -4mA -4mA -4mA -4mA -4mB -4mB -4mB -4mB -4mB -4mB -4mB -4mB	Series	MediaSensor?
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Sealed Gauge
Output 4 mA ~ 20 mA  Accuracy ±1%  Voltage - Supply 8 V ~ 30 V  Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Cable 1'  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	15 PSI (103.42 kPa)
Accuracy $\pm 1\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Cable 1'  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Current
Voltage - Supply  8 V ~ 30 V  Port Size  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Cable 1'  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	4 mA ~ 20 mA
Port Size  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Cable 1'  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package	Accuracy	±1%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Cable 1'  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated  Termination Style Cable 1'  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Female - M10 x 1.25
Termination Style Cable 1'  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Cable 1'
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

### P51-15-S-L-I12-20MA-000-000 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-15-S-L-I12-20MA-000-000 Payment Methods



















## P51-15-S-L-I12-20MA-000-000 Shipping Methods













If you have any question about P51-15-S-L-I12-20MA-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com