

P51-15-S-N-P-20MA

P51-15-S-N-P-20MA Information

Heisener.com	 P51-15-S-N-P-20MA SSI Technologies Inc Sensors, Transducers Pressure Sensors, Transducers SENSOR 15PSIS 1.2 UNF 4-20MA Cylinder For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



P51-15-S-N-P-20MA Specifications

Manufacturer Part NumberP51-15-S-N-P-20MAManufacturerSSI Technologies IncCategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOutput TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±1%Yoltage - SupplySeriedPort SizeIrreadedPort SizeAmplified Output, Temperature CompensatedFeaturesAmplified Output, Temperature CompensatedPort StyleSeried Output, Temperature Compensated <th></th>	
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Yoltage - SupplySa V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Output Pressure-Accuracy9 C ~ 105°C	
Pressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Analog Curent-Amplified Output, Temperature CompensatedFeatures-Analog Curent-Analog Curent-Amplified Output, Temperature CompensatedFeatures-Analog Curent-Analog Curent-Analog Curent-Amplified Output, Temperature CompensatedFeatures-Analog Curent-Analog Curent- <td></td>	
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput Queut4 mA ~ 20 mAAccuracy±1%Yoltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Operating	
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Pressure TypeSealed GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAnalified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Operating Pressure15 PSI (103.42 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure-Operating Temperature-Operating Te	
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure-Operating Temperature-40°C ~ 105°C	
Output4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure-Operating Temperature-40°C ~ 105°C	
Accuracy±1%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Port Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
FeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Termination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°C	
Maximum Pressure-Operating Temperature-40°C ~ 105°C	
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	
Package / Case Cylinder	
Supplier Device Package -	
	Report errors?

P51-15-S-N-P-20MA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-15-S-N-P-20MA Payment Methods



P51-15-S-N-P-20MA Shipping Methods



If you have any question about P51-15-S-N-P-20MA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com