

P51-1500-A-P-M12-20MA-000-000

P51-1500-A-P-M12-20MA-000-000 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



P51-1500-A-P-M12-20MA-000-000 Specifications

Manufacturer Part NumberP51-1500-A-P-M12-20MA-000-000ManufacturerSSI Technologies IncCategorySensors, TransducersPackageOylinderPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - SupplySt V ~ 30 VPort SizeMale - M20 x 1.5Port SiyleAmplified Output, Temperature CompensatedFeaturesMilfied Output, Temperature CompensatedMaximu Pressure4002 a 10500		
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeThreadedPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-	Manufacturer Part Number	P51-1500-A-P-M12-20MA-000-000
Pressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure.	Manufacturer	SSI Technologies Inc
PackageCylinderPerskageMediaSensor?Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style.Maximum Pressure.	Package	Cylinder
Operating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Series	MediaSensor?
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Pressure Type	Absolute
Output4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Operating Pressure	1500 PSI (10342.14 kPa)
Accuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Output Type	Analog Current
Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Output	4 mA ~ 20 mA
Port SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Accuracy	$\pm 0.5\%$
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Voltage - Supply	8 V ~ 30 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-	Port Size	Male - M20 x 1.5
Termination Style M12, 4 Pin Maximum Pressure -	Port Style	Threaded
Maximum Pressure -	Features	Amplified Output, Temperature Compensated
	Termination Style	M12, 4 Pin
0 / T / (1050G	Maximum Pressure	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Package / Case Cylinder	Package / Case	Cylinder
Supplier Device Package -	Supplier Device Package	-
Report e		Report errors?

P51-1500-A-P-M12-20MA-000-000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-1500-A-P-M12-20MA-000-000 Payment Methods WIRE transfer PayPai Methods P51-1500-A-P-M12-20MA-000-000 Shipping Methods FECEX. M TOND TOND OF STATES

If you have any question about P51-1500-A-P-M12-20MA-000-000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com