



Heisener.com

### P51-1500-S-T-P-4.5V-000-000 Information

Part Number P51-1500-S-T-P-4.5V-000-000

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 1500PSI 7/16-20-2B 4.5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# P51-1500-S-T-P-4.5V-000-000 Specifications

Manufacturer Part Number         P51-1500-S-T-P-4.5V-000-000           Manufacturer         SSI Technologies Inc           Category         Sensors, Transducers           Package         Cylinder           Series         MediaSensor?           Pressure Type         Sealed Gauge           Operating Pressure         1500 PSI (10342.14 kPa)           Output Type         Analog Voltage           Output         0.5 V ~ 4.5 V           Accuracy         ±0.5%           Voltage - Supply         5V           Port Size         Female - 7/16" (11.11mm) UNF           Port Style         Threaded           Features         Amplified Output, Temperature Compensated           Termination Style         Packard, 3 Pin           Maximum Pressure         -           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-1500-S-T-P-4.5V-000-000
Package Cylinder  Series MediaSensor?  Pressure Type Sealed Gauge  Operating Pressure  Operating Pressure  Output Type Analog Voltage  Output  Accuracy ±0.5%  Voltage - Supply  Port Size Female - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Supplier Device Package  -  Cylinder  Pressure Sealed Gauge  MediaSensors, Transducers  MediaSensors, Transducers  It ransducers  MediaSensors, Transducers  MediaSensors  MediaSens	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure1500 PSI (10342.14 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure 1500 PSI (10342.14 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Female - 7/16" (11.11mm) UNF Port Size Female - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package -	Package	Cylinder
Operating Pressure  1500 PSI (10342.14 kPa)  Analog Voltage  Output  0.5 V ~ 4.5 V  Accuracy  ±0.5%  Voltage - Supply  5V  Port Size  Female - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Supplier Device Package  -  Cylinder	Series	MediaSensor?
Output Type	Pressure Type	Sealed Gauge
Output 0.5 V ~ 4.5 V  Accuracy ±0.5%  Voltage - Supply 5V  Port Size Female - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	1500 PSI (10342.14 kPa)
Accuracy ±0.5%  Voltage - Supply 5V  Port Size Female - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  Fort Size  Female - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	0.5 V ~ 4.5 V
Port Size Female - 7/16" (11.11mm) UNF  Port Style Threaded Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	5V
Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Female - 7/16" (11.11mm) UNF
Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Packard, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P51-1500-S-T-P-4.5V-000-000 Guarantees



# **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### P51-1500-S-T-P-4.5V-000-000 Payment Methods



















# P51-1500-S-T-P-4.5V-000-000 Shipping Methods













If you have any question about P51-1500-S-T-P-4.5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com