

P51-200-G-N-I36-5V Information

Heisener.com

Part NumberP51-200-G-N-I36-5VManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 200PSI 1.2-20UNF-2A 1-5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-200-G-N-I36-5V Specifications

Manufacturer Part Number P51-200-G-N-136-5V Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Vented Gauge Operating Pressure 200 PSI (1378.95 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 3'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-200-G-N-I36-5V
Package Cylinder Series MediaSensor? Pressure Type Vented Gauge Operating Pressure Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 3'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure200 PSI (1378.95 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 3'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 200 PSI (1378.95 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure 200 PSI (1378.95 kPa) Output Type Analog Voltage Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C $\sim 105^{\circ}\text{C}$ Package / Case Cylinder Supplier Device Package -	Series	MediaSensor?
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 3'Maximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Pressure Type	Vented Gauge
Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 3'Maximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	200 PSI (1378.95 kPa)
Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output	1 V ~ 5 V
Port Size - Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package	Accuracy	±0.5%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	-
Termination Style Cable 3' Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Termination Style	Cable 3'
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
1. op 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1		Report errors?

P51-200-G-N-I36-5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-200-G-N-I36-5V Payment Methods



















P51-200-G-N-I36-5V Shipping Methods













If you have any question about P51-200-G-N-I36-5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com