

## P51-2000-A-AD-I12-5V-000-000 Information

Heisener.com	 P51-2000-A-AD-I12-5V-000-000 SSI Technologies Inc Sensors, Transducers Pressure Sensors, Transducers SENS 2000PSI 22MM 7/16-20 UNF 5V Cylinder For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## P51-2000-A-AD-I12-5V-000-000 Specifications

Manufacturer Part Number     P51-2000-AAD-112-5V-000-000       Manufacturer     SSI Technologies Inc       Category     Sensors, Transducers       Pressure Sensors, Transducers     Pressure Sensors, Transducers       Package     Cylinder       Series     MediaSensor?       Pressure Type     Absolute       Operating Pressure     2000 PSI (13789.51 kPa)       Output Type     Analog Voltage       Output Type     Analog Voltage       Output     1 V ~ 5 V       Accuracy     405.5%       Voltage - Supply     8 V ~ 30 V       Presded     Threaded       Features     Amplified Output, Temperature Compensated       Termination Style     Cable 1'       Maximum Pressure     -       Operating Temperature     40°C ~ 105°C       Package / Case     Cylinder		
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort SyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Supplier Device Package-Supplier Device Package-	Manufacturer Part Number	P51-2000-A-AD-I12-5V-000-000
Pressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput Que1 V ~ 5 VAccuracy±0.5%Voltage Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature40°C ~ 105°CPackage / Case-Supplier Device Package-	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale 7.716" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature40°C ~ 105°CPackage / CaseSilmerSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput Que1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature-Spring Temperature-Operating Temperature-Spring Temperat		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput Q1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-Supplier Device Package-	Package	Cylinder
Operating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutputI V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Series	MediaSensor?
Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Absolute
Output1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	2000 PSI (13789.51 kPa)
Acuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output Type	Analog Voltage
Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output	1 V ~ 5 V
Port SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Accuracy	$\pm 0.5\%$
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Voltage - Supply	8 V ~ 30 V
FeaturesAmplified Output, Temperature CompensatedFeaturesCable 1'Termination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Size	Male - 7/16" (11.11mm) UNF
Termination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-Supplier Device Package-	Termination Style	Cable 1'
Package / Case Cylinder   Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	$-40^{\circ}$ C ~ $105^{\circ}$ C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

### P51-2000-A-AD-I12-5V-000-000 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# P51-2000-A-AD-I12-5V-000-000 Payment Methods WIRE PayPar PayPar Methods P51-2000-A-AD-I12-5V-000-000 Shipping Methods P51-2000-A-AD-I12-5V-000-000 Shipping Methods P51-2000-A-AD-I12-5V-000-000 Shipping Methods

If you have any question about P51-2000-A-AD-I12-5V-000-000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com