

P51-3000-A-N-D-5V Information

Heisener.com

Part NumberP51-3000-A-N-D-5VManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 3000PSI 1.2-20 UNF-2A 5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-3000-A-N-D-5V Specifications

Manufacturer Part Number P51-3000-A-N-D-5V Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 3000 PSI (20684.27 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -			
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure3000 PSI (20684.27 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-3000-A-N-D-5V	
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package Perssure Supson MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors Med	Manufacturer	SSI Technologies Inc	
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure3000 PSI (20684.27 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers	
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure3000 PSI (20684.27 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Operating Pressure 3000 PSI (20684.27 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder	Package	Cylinder	
Operating Pressure 3000 PSI (20684.27 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder	Series	MediaSensor?	
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Pressure Type	Absolute	
Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	3000 PSI (20684.27 kPa)	
Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Voltage	
Voltage - Supply Port Size Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output	1 V ~ 5 V	
Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.5%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	-	
Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded	
Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Deutsch, 3 Pin	
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-	
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C	
	Package / Case	Cylinder	
	Supplier Device Package	-	
Report errors?		R	eport errors?

P51-3000-A-N-D-5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-3000-A-N-D-5V Payment Methods



















P51-3000-A-N-D-5V Shipping Methods













If you have any question about P51-3000-A-N-D-5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com