



#### P51-3000-S-N-P-4.5V Information

Heisener.com

Part Number P51-3000-S-N-P-4.5V Manufacturer SSI Technologies Inc Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 3000PSI 1.2-20UNF-2A 4.5V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## P51-3000-S-N-P-4.5V Specifications

Manufacturer Part Number       P51-3000-S-N-P-4.5V         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Sealed Gauge         Operating Pressure       3000 PSI (20684.27 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.5%         Voltage - Supply       5V         Port Size       -         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Packard, 3 Pin         Maximum Pressure       -         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
Category         Sensors, Transducers           Package         Cylinder           Series         MediaSensor?           Pressure Type         Sealed Gauge           Operating Pressure         3000 PSI (20684.27 kPa)           Output Type         Analog Voltage           Output         0.5 V ~ 4.5 V           Accuracy         ±0.5%           Voltage - Supply         5V           Port Size         -           Port Style         Threaded           Features         Amplified Output, Temperature Compensated           Termination Style         Packard, 3 Pin           Maximum Pressure         -           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -	Manufacturer Part Number	P51-3000-S-N-P-4.5V
Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Package Apin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure3000 PSI (20684.27 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure3000 PSI (20684.27 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure 3000 PSI (20684.27 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cutput - Sealed Gauge 3000 PSI (20684.27 kPa) - Analog Voltage - 5V V Analog Voltage	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Fort Size - Port Style Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cutput Analog Voltage Analog Voltage - Analog	Series	MediaSensor?
Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output 0.5 V ~ 4.5 V  Accuracy ±0.5%  Voltage - Supply 5V  Port Size - Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	3000 PSI (20684.27 kPa)
Accuracy ±0.5%  Voltage - Supply 5V  Port Size -  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  Port Size  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	0.5 V ~ 4.5 V
Port Size - Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	$\pm 0.5\%$
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	5V
Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	-
Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Packard, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P51-3000-S-N-P-4.5V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### P51-3000-S-N-P-4.5V Payment Methods



















# P51-3000-S-N-P-4.5V Shipping Methods













If you have any question about P51-3000-S-N-P-4.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com