



Heisener.com

P51-50-S-P-P-20MA-000-000 Information

Part Number P51-50-S-P-P-20MA-000-000

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 50PSIS M20 4-20MA

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-50-S-P-P-20MA-000-000 Specifications

Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure - 40°C ~ 105°C		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package	Manufacturer Part Number	P51-50-S-P-P-20MA-000-000
Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature - 40°C ~ 105°C Package / Case Cylinder Supplier Device Package - Cylinder	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure50 PSI (344.74 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±1%Voltage - Supply8 V ~ 30 VPort SizeMale - M20 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cutyput Analog Current Amalog Current Am	Series	MediaSensor?
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Sealed Gauge
Output 4 mA ~ 20 mA Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Operating Pressure	50 PSI (344.74 kPa)
Accuracy ±1% Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Current
Voltage - Supply 8 V ~ 30 V Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Supplier Device Package	Output	4 mA ~ 20 mA
Port Size Male - M20 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±1%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - M20 x 1.5
Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Termination Style	Packard, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

P51-50-S-P-P-20MA-000-000 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-50-S-P-P-20MA-000-000 Payment Methods



















P51-50-S-P-P-20MA-000-000 Shipping Methods













If you have any question about P51-50-S-P-P-20MA-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com