

### P51-75-A-R-MD-20MA-000-000 Information



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## P51-75-A-R-MD-20MA-000-000 Specifications

Manufacturer Part NumberP51-75-A-R-MD-20MA-000-000ManufacturerSIS Technologies IncCategorySensors, TransducersPackageQylinderPackageMediaSensor, TransducersPressure TypeAbsoluteOperating PressureAbsoluteOutput TypeAnalog CurrentOutput Que35 NS I (S17.11 kPa)Output Que40% - 20 mAYoltage - SupplySi No NPort SizeMale - M12 x 1.0Port SizeMale - M12 x 1.0PacturesMulfield Output, TemperaturePresureMulfield Output, TemperaturePort SizeMulfield Output, TemperaturePactage / Case-Output Presure-Pactage / Case-Output Package-Package / Case-Supplier Device Package-Supplier D		
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput Que4 mA ~ 20 mAAccuracy40.5%Voltage - Supply8V ~ 30 VPort SizeThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Operating Consert-Maximum Pressure-Operating Temperature-Operating Temperature-<	nufacturer Part Number	P51-75-A-R-MD-20MA-000-000
PackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature40°C ~ 105°CPackage / CaseCylinder	nufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAOutput±0.5%Yoltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderOtip CaseCylinder	egory	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Operating Temperature-Operature-Ope		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaxinum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	kage	Cylinder
Operating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	es	MediaSensor?
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	ssure Type	Absolute
Output4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	rating Pressure	75 PSI (517.11 kPa)
Accuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	put Type	Analog Current
Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	put	4 mA ~ 20 mA
Port SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	uracy	±0.5%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	tage - Supply	8 V ~ 30 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	Size	Male - M12 x 1.0
Termination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	tStyle	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	tures	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 105°CPackage / CaseCylinder	mination Style	MD, 4 Pin
Package / Case Cylinder	kimum Pressure	-
	rating Temperature	$-40^{\circ}$ C ~ $105^{\circ}$ C
Supplier Device Package -	kage / Case	Cylinder
	plier Device Package	-
Report		Report errors?

### P51-75-A-R-MD-20MA-000-000 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about P51-75-A-R-MD-20MA-000-000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com