



Heisener.com

#### P51-75-G-L-P-4.5V-000-000 Information

**Part Number** P51-75-G-L-P-4.5V-000-000

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 75PSI M10-1.25 6H .5-4.5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# P51-75-G-L-P-4.5V-000-000 Specifications

Manufacturer Part Number       P51-75-G-L-P-4.5V-000-000         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Vented Gauge         Operating Pressure       75 PSI (517.11 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.5%         Voltage - Supply       5V         Port Size       Female - M10 x 1.25         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Packard, 3 Pin         Maximum Pressure       -         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-75-G-L-P-4.5V-000-000
Package Cylinder  Series MediaSensor?  Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output Outp	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 75 PSI (517.11 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder	Series	MediaSensor?
Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Vented Gauge
Output 0.5 V ~ 4.5 V  Accuracy ±0.5%  Voltage - Supply 5V  Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	75 PSI (517.11 kPa)
Accuracy ±0.5%  Voltage - Supply 5V  Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  - Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	0.5 V ~ 4.5 V
Port Size  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  - Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	5V
Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Female - M10 x 1.25
Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Packard, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P51-75-G-L-P-4.5V-000-000 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-75-G-L-P-4.5V-000-000 Payment Methods





















### P51-75-G-L-P-4.5V-000-000 Shipping Methods













If you have any question about P51-75-G-L-P-4.5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com