



### P51-75-G-N-P-20MA Information

Heisener.com

Part NumberP51-75-G-N-P-20MAManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 75PSI 1.2-20UNF-2A 4-20MA

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## P51-75-G-N-P-20MA Specifications

Manufacturer Part Number       P51-75-G-N-P-20MA         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Vented Gauge         Operating Pressure       75 PSI (517.11 kPa)         Output Type       Analog Current         Output       4 mA ~ 20 mA         Accuracy       ±0.5%         Voltage - Supply       8 V ~ 30 V         Port Size       -         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Packard, 3 Pin         Maximum Pressure       -         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-75-G-N-P-20MA
Package Cylinder Series MediaSensor? Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package - Cylinder Sure	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeVented GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort Size-Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 75 PSI (517.11 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder	Series	MediaSensor?
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V  Port Size - Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Vented Gauge
Output 4 mA ~ 20 mA  Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size - Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	75 PSI (517.11 kPa)
Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size -  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Current
Voltage - Supply  Port Size  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard, 3 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	4 mA ~ 20 mA
Port Size - Threaded Features Amplified Output, Temperature Compensated Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated  Termination Style Packard, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	-
Termination Style Packard, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Packard, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P51-75-G-N-P-20MA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-75-G-N-P-20MA Payment Methods



















## P51-75-G-N-P-20MA Shipping Methods













If you have any question about P51-75-G-N-P-20MA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com