

Heisener.com

P51-75-S-C-I12-20MA-000-000

P51-75-S-C-I12-20MA-000-000 Information

Part Number P51-75-S-C-I12-20MA-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

Description SENSOR 75PSIS M12 4-20 MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-75-S-C-I12-20MA-000-000 Specifications

Manufacturer Part NumberP51-75-S-C-112-20MA-000-000ManufacturerSSI Technologies IncCategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-Operating Temperature-40°C ~ 105°C		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-	Manufacturer Part Number	P51-75-S-C-I12-20MA-000-000
Pressure Sensors, Transducers Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure Cylinder Sensors, Transducers Cylinder Adela Sensors, Transducers MediaSensor, Transducers MediaSensor, Transducers Analog Current 4 mA ~ 20 mA 4 mA ~ 20 mA 4 mA ~ 20 mA 5 V ~ 30 V Port Size Male - M12 x 1.5 Port Style Threaded Features - Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure -	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure75 PSI (517.11 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-	Category	Sensors, Transducers
Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure 75 PSI (517.11 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure -		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 75 PSI (517.11 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.5 Port Style Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure -	Package	Cylinder
Operating Pressure 75 PSI (517.11 kPa) Output Type Analog Current 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.5 Port Style Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure -	Series	MediaSensor?
Output TypeAnalog CurrentOutput $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-	Pressure Type	Sealed Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleCable 1'Maximum Pressure-	Operating Pressure	75 PSI (517.11 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - M12 \times 1.5$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Cable 1'$ Maximum Pressure $-$	Output Type	Analog Current
Voltage - Supply $8 \ V \sim 30 \ V$ Port Size $Male - M12 \ x \ 1.5$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Cable \ 1'$ Maximum Pressure $-$	Output	4 mA ~ 20 mA
Port Size Male - M12 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure -	Accuracy	±0.5%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style Cable 1' Maximum Pressure -	Port Size	Male - M12 x 1.5
Termination Style Cable 1' Maximum Pressure -	Port Style	Threaded
Maximum Pressure -	Features	Amplified Output, Temperature Compensated
	Termination Style	Cable 1'
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Maximum Pressure	-
operating reinperature	Operating Temperature	-40°C ~ 105°C
Package / Case Cylinder	Package / Case	Cylinder
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

P51-75-S-C-I12-20MA-000-000 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-75-S-C-I12-20MA-000-000 Payment Methods



















P51-75-S-C-I12-20MA-000-000 Shipping Methods













If you have any question about P51-75-S-C-I12-20MA-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com