



Heisener.com

P51-750-A-AA-D-5V-000-000 Information

Part Number P51-750-A-AA-D-5V-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

Description SENSOR 750PSI 7/16-20 UNF 1-5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-750-A-AA-D-5V-000-000 Specifications

Manufacturer Part Number P51-750-A-AA-D-5V-000-000 Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-750-A-AA-D-5V-000-000
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure -40°C ~ 105°C Package / Case Cylinder Supplier Device Package Perssure MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers MediaSensors, Transducers 450 PSI Sensors, Transducers MediaSensors, Transducers Medi	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure $750 PSI (5171.07 kPa)$ Output TypeAnalog VoltageOutput $1 V \sim 5 V$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 V \sim 30 V$ Port SizeMale - $7/16'' (11.11 mm) UNF$ Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, $3 Pin$ Maximum Pressure-Operating Temperature $-40^{\circ}C \sim 105^{\circ}C$ Package / CaseCylinderSupplier Device Package-	Series	MediaSensor?
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Pressure Type	Absolute
Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 7/16'' (11.11 \text{mm}) \text{ UNF}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Deutsch, 3 \text{ Pin}$ Maximum Pressure $-$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $Cylinder$ Supplier Device Package $-$	Output Type	Analog Voltage
Voltage - Supply 8 V ~ 30 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output	1 V ~ 5 V
Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 7/16" (11.11mm) UNF
Termination Style Deutsch, 3 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Deutsch, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

P51-750-A-AA-D-5V-000-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-750-A-AA-D-5V-000-000 Payment Methods



















P51-750-A-AA-D-5V-000-000 Shipping Methods













If you have any question about P51-750-A-AA-D-5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com