

Heisener.com

# P51-750-A-L-M12-20MA-000-000

### P51-750-A-L-M12-20MA-000-000 Information

Part Number P51-750-A-L-M12-20MA-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

**Description** SENSOR 750PSI M10-1.25 6H 4-20MA

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### P51-750-A-L-M12-20MA-000-000 Specifications

Manufacturer Part Number         P51-750-A-L-M12-20MA-000-000           Manufacturer         SSI Technologies Inc           Category         Sensors, Transducers           Package         Cylinder           Series         MediaSensor?           Pressure Type         Absolute           Operating Pressure         750 PSI (5171.07 kPa)           Output Type         Analog Current           Output         4 mA ~ 20 mA           Accuracy         ±0.5%           Voltage - Supply         8 V ~ 30 V           Port Size         Female - M10 x 1.25           Port Style         Threaded           Features         Amplified Output, Temperature Compensated           Termination Style         M12, 4 Pin           Maximum Pressure         -           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-750-A-L-M12-20MA-000-000
Package Cylinder  Series MediaSensor?  Pressure Type Absolute Operating Pressure Operating Pressure Analog Current Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style M12, 4 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package  - Cylinder Supplier Device Package  - Cylinder  Pressure Adsolute MediaSensors, Transducers  MediaSensors, Transducers  Absolute Pressure Suplute Analog Current An	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeFemale - M10 x 1.25Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleM12, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Absolute Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style M12, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package  750 PSI (5171.07 kPa) Analog Current Amalog Current 4 mA ~ 20 mA 4 mA ~ 20 mA 4 mA 4 mA ~ 20 mA 4	Series	MediaSensor?
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Female - M10 x 1.25 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style M12, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Absolute
Output 4 mA ~ 20 mA  Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style M12, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size Female - M10 x 1.25  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style M12, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Current
Voltage - Supply  8 V ~ 30 V  Port Size  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  M12, 4 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	4 mA ~ 20 mA
Port Size  Female - M10 x 1.25  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  M12, 4 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style M12, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated  Termination Style M12, 4 Pin  Maximum Pressure -  Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case Cylinder  Supplier Device Package -	Port Size	Female - M10 x 1.25
Termination Style M12, 4 Pin  Maximum Pressure -  Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	M12, 4 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

### P51-750-A-L-M12-20MA-000-000 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-750-A-L-M12-20MA-000-000 Payment Methods



















## P51-750-A-L-M12-20MA-000-000 Shipping Methods













If you have any question about P51-750-A-L-M12-20MA-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com