

Heisener.com

P51-750-A-R-MD-5V-000-000

P51-750-A-R-MD-5V-000-000 Information

Part Number P51-750-A-R-MD-5V-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

Description SENSOR 750PSI M12-1.0 6G 1-5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P51-750-A-R-MD-5V-000-000 Specifications

Manufacturer Part NumberP51-750-A-R-MD-5V-000-000ManufacturerSSI Technologies IncCategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 Pin		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Manufacturer Part Number	P51-750-A-R-MD-5V-000-000
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Voltage Output 1 V ~ 5 V Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.0 Port Style Features Pressure Sensors, Transducers MediaSensor, AdeiaSensor, Absolute 750 PSI (5171.07 kPa) Analog Voltage 750 PSI (5171.07 kPa) 40.5% Analog Voltage 40.5% Threaded Threaded Amplified Output, Temperature Compensated	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure $750 \text{ PSI } (5171.07 \text{ kPa})$ Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Package	Cylinder
Operating Pressure $750 \text{ PSI } (5171.07 \text{ kPa})$ Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Series	MediaSensor?
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Pressure Type	Absolute
Output $1 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature Compensated	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - M12 \times 1.0$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$	Output Type	Analog Voltage
Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - M12 \times 1.0$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$	Output	1 V ~ 5 V
Port Size Male - M12 x 1.0 Port Style Threaded Features Amplified Output, Temperature Compensated	Accuracy	±0.5%
Port Style Threaded Features Amplified Output, Temperature Compensated	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated	Port Size	Male - M12 x 1.0
	Port Style	Threaded
Termination Style MD, 4 Pin	Features	Amplified Output, Temperature Compensated
	Termination Style	MD, 4 Pin
Maximum Pressure -	Maximum Pressure	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-40°C ~ 105°C
Package / Case Cylinder	Package / Case	Cylinder
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

P51-750-A-R-MD-5V-000-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P51-750-A-R-MD-5V-000-000 Payment Methods





















P51-750-A-R-MD-5V-000-000 Shipping Methods













If you have any question about P51-750-A-R-MD-5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com