



Heisener.com

#### P51-750-S-D-D-4.5V-000-000 Information

Part Number P51-750-S-D-D-4.5V-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

**Description** SENSOR 750PSI 7/16-20 UNF 4.5V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# P51-750-S-D-D-4.5V-000-000 Specifications

Manufacturer Part Number       P51-750-S-D-D-4.5V-000-000         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Sealed Gauge         Operating Pressure       750 PSI (5171.07 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.5%         Voltage - Supply       5V         Port Size       Male - 7/16" (11.11mm) UNF         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Deutsch, 3 Pin         Maximum Pressure       -         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-750-S-D-D-4.5V-000-000
Package Cylinder  Series MediaSensor?  Pressure Type Sealed Gauge  Operating Pressure Operating Pressure Output Type Analog Voltage  Output Ou	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Fort Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Fort Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Cylinder Supplier Device Package - Cotton Analog Voltage Analog Voltage - Cotton kPa - Analog Voltage - To PSI (5171.07 kPa) Analog Voltage - Cotton kPa - Analog Voltage - Cotton kPa - Analog Voltage - Cotton kPa - Accuracy - Analog Voltage - Cotton kPa - Accuracy - Analog Voltage - Cotton kPa - Accuracy - Analog Voltage - Cotton kPa - Cotton kP	Series	MediaSensor?
Output Type	Pressure Type	Sealed Gauge
Output 0.5 V ~ 4.5 V  Accuracy ±0.5%  Voltage - Supply 5V  Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Deutsch, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy ±0.5%  Voltage - Supply 5V  Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Deutsch, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  5V  Port Size  Male - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Deutsch, 3 Pin  Maximum Pressure  - Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	0.5 V ~ 4.5 V
Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Deutsch, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Deutsch, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	5V
Features Amplified Output, Temperature Compensated  Termination Style Deutsch, 3 Pin  Maximum Pressure - Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Male - 7/16" (11.11mm) UNF
Termination Style Deutsch, 3 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Deutsch, 3 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P51-750-S-D-D-4.5V-000-000 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P51-750-S-D-D-4.5V-000-000 Payment Methods



















# P51-750-S-D-D-4.5V-000-000 Shipping Methods













If you have any question about P51-750-S-D-D-4.5V-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com