

P51-750-S-M-MD-4.5OVP-000-000 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



P51-750-S-M-MD-4.5OVP-000-000 Specifications

Manufacturer Part Number P51-750-S-M-MD-4.50VP-000-000 Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Package Seled Gauge Sor Syle Seled Gauge Output Type Analog Voltage Output Type Analog Voltage Output Type Sol Syle Voltage - Supply Sol Sol Sol Sol Sol Voltage - Supply Sol Sol Port Size Mali Anulo X 1.0 Premiation Style Maplified Output, Temperature Compensated Package / Case Sol Sol Col Sol Port Size Mol A Pin Package / Case Cylinder		
CategorySensors, TransducersPackageCylinderPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type0.5 V ~ 4.5 VAccuracy±0.5%Voltage - SupplySvPort SizeMale - M10 x 1.0Port SizeMaplified Output, Temperature CompensatedPerturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-Port SizeCylinderSurger CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-750-S-M-MD-4.50VP-000-000
Pressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature40°C ~ 105°CPackage / Case.Supplier Device Package-	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure70 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type0.5 V ~ 4.5 VAccuracy±0.5%Voltage - SupplySVPort SizeMale - M10 x 1.0Port SizeIrreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CasecylinderSupplier Device Package-Supplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type0.5 V ~ 4.5 VAccuracy±0.5%Yoltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature-Supplier Device Package-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Quest0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Package	Cylinder
Operating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Series	MediaSensor?
Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Accuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	750 PSI (5171.07 kPa)
Acuracy±0.5%Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output Type	Analog Voltage
Voltage - Supply5VPort SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output	0.5 V ~ 4.5 V
Port SizeMale - M10 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Accuracy	$\pm 0.5\%$
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Voltage - Supply	5V
FeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Size	Male - M10 x 1.0
Termination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-Supplier Device Package-	Termination Style	MD, 4 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

P51-750-S-M-MD-4.5OVP-000-000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about P51-750-S-M-MD-4.5OVP-000-000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com