

Heisener.com

# P51-750-S-R-MD-20MA-000-000

### P51-750-S-R-MD-20MA-000-000 Information

Part Number P51-750-S-R-MD-20MA-000-000

Manufacturer SSI Technologies Inc Sensors, Transducers Category

Pressure Sensors, Transducers

SENSOR 750PSIS M12 4-20 MA **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# P51-750-S-R-MD-20MA-000-000 Specifications

Manufacturer Part Number       P51-750-S-R-MD-20MA-000-000         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Sealed Gauge         Operating Pressure       750 PSI (5171.07 kPa)         Output Type       Analog Current         Output       4 mA ~ 20 mA         Accuracy       ±0.5%         Voltage - Supply       8 V ~ 30 V         Port Size       Male - M12 x 1.0         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       MD, 4 Pin         Maximum Pressure       -         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P51-750-S-R-MD-20MA-000-000
Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.0 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package  Cylinder  Possure Sensors, Transducers  MediaSensors, Transducers  MediaSensors, Transducers  MediaSensors, Transducers  MediaSensor, Transducers  Analog Current  4 mA ~ 20 mA  4 mA ~	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - M12 x 1.0Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleMD, 4 PinMaximum Pressure-Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.0 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package	Package	Cylinder
Operating Pressure 750 PSI (5171.07 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.0 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Series	MediaSensor?
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - M12 x 1.0 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style MD, 4 Pin Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Sealed Gauge
Output 4 mA ~ 20 mA  Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size Male - M12 x 1.0  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style MD, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy $\pm 0.5\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - M12 \times 1.0$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $MD, 4 \text{ Pin}$ Maximum Pressure $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $Cylinder$ Supplier Device Package $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Output Type	Analog Current
Voltage - Supply  Port Size  Male - M12 x 1.0  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  MD, 4 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Output	4 mA ~ 20 mA
Port Size Male - M12 x 1.0  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style MD, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style MD, 4 Pin  Maximum Pressure -  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features  Amplified Output, Temperature Compensated  MD, 4 Pin  Maximum Pressure  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package  -	Port Size	Male - M12 x 1.0
Termination Style MD, 4 Pin  Maximum Pressure -  Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	MD, 4 Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
**	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
The post of the state of the st		Report errors?

#### P51-750-S-R-MD-20MA-000-000 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## P51-750-S-R-MD-20MA-000-000 Payment Methods



















# P51-750-S-R-MD-20MA-000-000 Shipping Methods













If you have any question about P51-750-S-R-MD-20MA-000-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com