

## P61-100-S-A-I24-20MA-A Information

Heisener.com	 P61-100-S-A-I24-20MA-A SSI Technologies Inc Sensors, Transducers Pressure Sensors, Transducers SENSOR 100PSIS 1/4 NPT W/TEMP Cylinder For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# P61-100-S-A-I24-20MA-A Specifications

ManufacturerSSI Technologies IncCategorySensors, TransducersPressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style300 PSI (2068.43 kPa)Operating Temperature440°C ~ 105°CPackage / CaseCylinder		
CategorySensors, TransducersPackageCylinderPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Syle-Features-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	P61-100-S-A-I24-20MA-A
PackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style24" Integral HarnessMaximum Pressure.300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / Case.Supplier Device Package.	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Type4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-Supplier Device Package-	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Queue4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Package	Cylinder
Operating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Series	MediaSensor?
OutputAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseSupplier Device PackageSupplier Device Package-	Pressure Type	Sealed Gauge
Output4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	100 PSI (689.48 kPa)
Accuracy±0.5%Accuracy\$V ~ 30 VVoltage - SupplySV ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output Type	Analog Current
Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Accuracy	±0.5%
Port StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Voltage - Supply	8 V ~ 30 V
Features-Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style24" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Style	Threaded
Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	24" Integral Harness
Package / Case Cylinder   Supplier Device Package -	Maximum Pressure	300 PSI (2068.43 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

### P61-100-S-A-I24-20MA-A Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### P61-100-S-A-I24-20MA-A Payment Methods





If you have any question about P61-100-S-A-I24-20MA-A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com