



Heisener.com

P61-2000-S-A-I12-4.5V-C Information

Part Number P61-2000-S-A-I12-4.5V-C

Manufacturer SSI Technologies Inc Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 2000PSIS 1/4 NPT W/TEMP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P61-2000-S-A-I12-4.5V-C Specifications

Manufacturer Part Number P61-2000-S-A-I12-4.5V-C Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure 2000 PSI (13789.51 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P61-2000-S-A-I12-4.5V-C
Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure Output Type Analog Voltage Output (13789.51 kPa)	Manufacturer	SSI Technologies Inc
Package Cylinder Series MediaSensor? Pressure Type Sealed Gauge Operating Pressure 2000 PSI (13789.51 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply 5V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeSealed GaugeOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure2000 PSI (13789.51 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.5% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - 2000 PSI (13789.51 kPa) Analog Voltage 40.5 V Analog Voltage -40.5% Cylinder -40°C ~ 105°C	Series	MediaSensor?
Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.5%Voltage - Supply5VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply 5 V Port Size $\text{Male - 1/4" (6.35 mm) NPT}}$ Port Style $\text{Threaded}}$ Features - Termination Style 12 " Integral Harness Maximum Pressure $6000 \text{ PSI (41368.54 kPa)}}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $\text{Cylinder}}$	Operating Pressure	2000 PSI (13789.51 kPa)
Accuracy ±0.5% Voltage - Supply 5V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply Fort Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Supplier Device Package	Output	0.5 V ~ 4.5 V
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	5V
Features - 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style 12" Integral Harness Maximum Pressure 6000 PSI (41368.54 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure6000 PSI (41368.54 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	12" Integral Harness
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	6000 PSI (41368.54 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

P61-2000-S-A-I12-4.5V-C Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P61-2000-S-A-I12-4.5V-C Payment Methods



















P61-2000-S-A-I12-4.5V-C Shipping Methods













If you have any question about P61-2000-S-A-I12-4.5V-C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com