



Heisener.com

P61-300-A-A-I18-20MA-C Information

Part Number P61-300-A-A-I18-20MA-C

ManufacturerSSI Technologies IncCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 300PSIA 1/4 NPT W/TEMP

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









P61-300-A-A-I18-20MA-C Specifications

Manufacturer Part Number P61-300-A-A-I18-20MA-C Manufacturer SSI Technologies Inc Category Sensors, Transducers Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog Current Output Quity 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style18" Integral HarnessMaximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	P61-300-A-A-I18-20MA-C
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package	Manufacturer	SSI Technologies Inc
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style18" Integral HarnessMaximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style18" Integral HarnessMaximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Supplier Device Package 300 PSI (2068.43 kPa) Analog Current 4 mA ~ 20 mA 4	Series	MediaSensor?
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style18" Integral HarnessMaximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Absolute
Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Operating Pressure	300 PSI (2068.43 kPa)
Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Current
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Supplier Device Package - Supplier Device Package	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded Features - Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features - 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style 18" Integral Harness Maximum Pressure 900 PSI (6205.28 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure900 PSI (6205.28 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package -	Termination Style	18" Integral Harness
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	900 PSI (6205.28 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

P61-300-A-A-I18-20MA-C Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

P61-300-A-A-I18-20MA-C Payment Methods

































If you have any question about P61-300-A-A-I18-20MA-C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com