

# P61-750-A-A-I24-5V-C

#### P61-750-A-A-I24-5V-C Information

Heisener.com	 P61-750-A-A-I24-5V-C SSI Technologies Inc Sensors, Transducers Pressure Sensors, Transducers SENSOR 750PSIA 1/4 NPT W/TEMP Cylinder For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## P61-750-A-A-I24-5V-C Specifications

CategorySensors, TransducersPackageCylinderPackageMediaSensor?SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeThreadedPresdedThreadedFeatures-Termination Style24" Integral HarnessOperating Temperature440°C ~ 105°C		
CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature+40°C ~ 105°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	P61-750-A-A-I24-5V-C
Pressure Sensors, TransducersPackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style24" Integral HarnessMaximum Pressure-250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Manufacturer	SSI Technologies Inc
PackageCylinderSeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Type1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Syle-Features-Termination Style250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-Supplier D	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Quest1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (1551.3.2 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput Que1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort Style-Features-Termination Style2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-Supplier Device Package-	Package	Cylinder
Operating Pressure750 PSI (5171.07 kPa)Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure-40°C ~ 105°COperating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Series	MediaSensor?
Output TypeAnalog VoltageOutput1 V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / Case-Supplier Device Package-	Pressure Type	Absolute
OutputI V ~ 5 VAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	750 PSI (5171.07 kPa)
Accuracy±0.5%Accuracy8 V ~ 30 VVoltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output Type	Analog Voltage
Yoltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Output	1 V ~ 5 V
Port SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Accuracy	±0.5%
Port StyleThreadedFeatures-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Voltage - Supply	8 V ~ 30 V
Features-Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style24" Integral HarnessMaximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Port Style	Threaded
Maximum Pressure2250 PSI (15513.2 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	24" Integral Harness
Package / Case Cylinder   Supplier Device Package -	Maximum Pressure	2250 PSI (15513.2 kPa)
Supplier Device Package -	Operating Temperature	$-40^{\circ}$ C ~ $105^{\circ}$ C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### P61-750-A-A-I24-5V-C Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### P61-750-A-A-I24-5V-C Payment Methods



#### P61-750-A-A-I24-5V-C Shipping Methods



If you have any question about P61-750-A-A-I24-5V-C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com