

# P6KE27CATA

### **P6KE27CATA Information**



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **P6KE27CATA Specifications**

Manufacturer Part NumberP6KE27CATAManufacturerSMC Diode SolutionsCategoryCircuit ProtectionTVS - DiodesTVS - DiodesPackageDo-204AC, DO-15, AxialSeriesP6KETypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Reverse Standoff (Typ)3.5.VVoltage - Clamping (Max) @ Ipp60WPower - Peak Pulse (10/1000µs)6.2APower Line ProtectionNoApplicationsGeneralPurposeOperating Tengensture-Operating Tengensture-ApplicationsGioreal PurposeApplications-Applications-Operating Tengensture-Applications- </th <th></th> <th></th>		
CategoryCircuit ProtectionTVS - DiodesPackageDO-204AC, DO-15, AxialSeriesD6KETypeZenerUnidrectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)57.7VVoltage - Clamping (Max) @ Ipp600WPower - Peak Pulse (10/100µs)16.2APower Line ProtectionNoApplicationsGeneral PurposeApplicationsGeneral PurposeOperating Frequency-ApplicationsGeneral PurposeMounting TypeHorogy HoleMounting TypeThrough HolePackage / CaseDO-204AC, DO-15, Axial	Manufacturer Part Number	P6KE27CATA
TVS - DiodesPackageDO-204AC, DO-15, AxialSeriesP6KETypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCurpating Temperature-Operating Temperature-Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Manufacturer	SMC Diode Solutions
PackageDO-204AC, DO-15, AxialSeriesP6KETypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)600WPower - Peak Pulse600WPower Jine ProtectionNoApplicationsGeneral PurposeCurpating Temperature-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeDo-204AC, DO-15, AxialPoupler Device PackageDO-204AC, DO-15, Axial	Category	Circuit Protection
SeriesP6KETypeZenerUndirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/100µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeOperating Temperature-Operating Temperature-Power Age Age-Stating Temperature-Operating Temperature-Double Device PackageDouble Device Dev		TVS - Diodes
TypeZenerUndirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/100µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, Axial	Package	DO-204AC, DO-15, Axial
TypeIntra-Unidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Series	P6KE
Bidirectional Channels1Bidirectional Channels1Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Туре	Zener
Voltage - Reverse Standoff (Typ)23.1VVoltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Unidirectional Channels	-
Voltage - Breakdown (Min)25.7VVoltage - Clamping (Max) @ Ipp37.5VCurrent - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Bidirectional Channels	1
Voltage - Clamping (Max) @ Ipp 37.5V   Current - Peak Pulse (10/1000µs) 16.2A   Power - Peak Pulse 600W   Power - Peak Pulse 600W   Power Line Protection No   Applications General Purpose   Capacitance @ Frequency -   Operating Temperature -65°C ~ 175°C (TJ)   Mounting Type Through Hole   Package / Case DO-204AC, DO-15, Axial	Voltage - Reverse Standoff (Typ)	23.1V
Current - Peak Pulse (10/1000µs)16.2APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Voltage - Breakdown (Min)	25.7V
Power - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Voltage - Clamping (Max) @ Ipp	37.5V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Current - Peak Pulse (10/1000µs)	16.2A
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Power - Peak Pulse	600W
Capacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Power Line Protection	No
Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Capacitance @ Frequency	-
Package / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-15	Operating Temperature	-65°C ~ 175°C (TJ)
Supplier Device Package DO-15	Mounting Type	Through Hole
	Package / Case	DO-204AC, DO-15, Axial
	Supplier Device Package	DO-15
Report erro		Report errors?

#### **P6KE27CATA Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **P6KE27CATA Payment Methods**



## **P6KE27CATA Shipping Methods**



If you have any question about P6KE27CATA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com