

P6KE350A-G

P6KE350A-G Information

www.helsenes.com		P6KE350A-G Comchip Technology Circuit Protection TVS - Diodes	回然 (1) 第55元[1]
×	Description	TVS DIODE 299.3VWM 482VC DO15	- AT - 529.
	Package	DO-204AC, DO-15, Axial	i i i kind na
		For the pricing/inventory/lead time, please contact us	er en
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



P6KE350A-G Specifications

Manufacturer Part NumberP6KE350A-GManufacturerComchip TechnologyCategoryCircuit ProtectionCategoryCircuit ProtectionFackageDO-204AC, DO-15, AxialPackage-Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)32.5VVoltage - Clamping (Max) @ Ipp1.24APower Line ProtectionNoApplicationsGeneral PurposePower Line ProtectionNoApplicationsGeneral PurposeConcine Tree Perpendency-Concine Tree PerpendencyConcort Tree Protection	
CategoryCircuit ProtectionTVS - DiodesPackageDO-204AC, DO-15, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
TVS - DiodesPackageDO-204AC, DO-15, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/100µs)1.24APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
PackageDO-204AC, DO-15, AxialSeries-TypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower Line ProtectionKoApplicationsGeneral PurposeCapacitance @ Frequency-	
Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower Line ProtectionKoApplicationsGeneral PurposeCapacitance @ Frequency-	
CypeInterferenceUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Bidirectional Channels-Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Voltage - Reverse Standoff (Typ)299.3VVoltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Voltage - Breakdown (Min)332.5VVoltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Voltage - Clamping (Max) @ Ipp482VCurrent - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Current - Peak Pulse (10/1000µs)1.24APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Power - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-	
ApplicationsGeneral PurposeCapacitance @ Frequency-	
Capacitance @ Frequency -	
Operating Temperature $-55^{\circ}\text{C} \sim 150^{\circ}\text{C} \text{(TJ)}$	
Mounting Type Through Hole	
Package / Case DO-204AC, DO-15, Axial	
Supplier Device Package DO-15	
Report	rrors

P6KE350A-G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

P6KE350A-G Payment Methods





If you have any question about P6KE350A-G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com