



## **PA4333.222NLT Information**

Part Number PA4333.222NLT

Manufacturer Pulse Electronics Power Category Inductors, Coils, Chokes

**Fixed Inductors** 

**Description FIXED IND 2.2UH 5.65A 18 MOHM** 

Package Nonstandard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PA4333.222NLT Specifications**

Manufacturer Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series PA4333 Type Wirewound Material - Core Inductance Inductance 2.2µH Tolerance 2.2µH Current Rating 5.65A Current - Saturation Shielding DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings -	
Fixed Inductors	
Package         Nonstandard           Series         PA4333           Type         Wirewound           Material - Core         Iron           Inductance         2.2μH           Tolerance         ±20%           Current Rating         5.65A           Current - Saturation         6.5A           Shielding         Shielded           DC Resistance (DCR)         18 mOhm Max           Q @ Freq         -           Frequency - Self Resonant         24MHz           Ratings         -	
Series         PA4333           Type         Wirewound           Material - Core         Iron           Inductance         2.2μH           Tolerance         ±20%           Current Rating         5.65A           Current - Saturation         6.5A           Shielding         Shielded           DC Resistance (DCR)         18 mOhm Max           Q @ Freq         -           Frequency - Self Resonant         24MHz           Ratings         -	
Type         Wirewound           Material - Core         Iron           Inductance         2.2μH           Tolerance         ±20%           Current Rating         5.65A           Current - Saturation         6.5A           Shielding         Shielded           DC Resistance (DCR)         18 mOhm Max           Q @ Freq         -           Frequency - Self Resonant         24MHz           Ratings         -	
Material - Core       Iron         Inductance       2.2μH         Tolerance       ±20%         Current Rating       5.65A         Current - Saturation       6.5A         Shielding       Shielded         DC Resistance (DCR)       18 mOhm Max         Q @ Freq       -         Frequency - Self Resonant       24MHz         Ratings       -	
Inductance         2.2μH           Tolerance         ±20%           Current Rating         5.65A           Current - Saturation         6.5A           Shielding         Shielded           DC Resistance (DCR)         18 mOhm Max           Q @ Freq         -           Frequency - Self Resonant         24MHz           Ratings         -	
Tolerance         ±20%           Current Rating         5.65A           Current - Saturation         6.5A           Shielding         Shielded           DC Resistance (DCR)         18 mOhm Max           Q @ Freq         -           Frequency - Self Resonant         24MHz           Ratings         -	
Current Rating 5.65A Current - Saturation 6.5A Shielding Shielded DC Resistance (DCR) 18 mOhm Max Q @ Freq - Frequency - Self Resonant 24MHz Ratings -	
Current - Saturation 6.5A Shielding Shielded DC Resistance (DCR) 18 mOhm Max Q @ Freq - Frequency - Self Resonant 24MHz Ratings -	
Shielding DC Resistance (DCR) 18 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings -	
DC Resistance (DCR)  18 mOhm Max  Q @ Freq  Frequency - Self Resonant  Ratings  -	
Q @ Freq - Frequency - Self Resonant 24MHz Ratings -	
Frequency - Self Resonant 24MHz Ratings -	
Ratings -	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Frequency - Test 1MHz	
Features -	
Mounting Type Surface Mount	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.291" L x 0.268" W (7.40mm x 6.80mm)	

Height - Seated (Max)	0.126" (3.20mm)
	Report errors?

#### **PA4333.222NLT Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **PA4333.222NLT Payment Methods**



















# **PA4333.222NLT Shipping Methods**













If you have any question about PA4333.222NLT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com