



PAM3101HCA330 Information



For Reference Only

Part Number PAM3101HCA330

Manufacturer Diodes Incorporated

Category Integrated Circuits (ICs)

PMIC - Voltage Regulators - Linear

Description IC REG LINEAR 3.3V 300MA SOT89-3

Package TO-243AA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PAM3101HCA330 Specifications

Manufacturer Part Number PAM3101HCA330 Manufacturer Diodes Incorporated Category Integrated Circuits (ICs) PaCkage TO-243AA Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5 V Voltage - Output (Min/Fixed) 3.3 V Voltage - Output (Max) - Voltage Dropout (Max) 0.23 V @ 300mA Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) 90μA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Over Current, Over Temperature, Short Circuit Operating Temperature 4.0°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3 Report errors?	•	
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package TO-243AA Scries - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5 V Voltage - Output (Min/Fixed) 3.3 V Voltage - Output (Max) - Voltage Dropout (Max) 0.23 V @ 300mA Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) 90μA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Manufacturer Part Number	PAM3101HCA330
Package TO-243AA Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Voltage Dropout (Max) 0.23V @ 300mA Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) 90μA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Manufacturer	Diodes Incorporated
Package TO-243AA Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Voltage Dropout (Max) 0.23V @ 300mA Current - Output 300mA Current - Quiescent (Iq) 90µA Current - Supply (Max) 90µA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Category	Integrated Circuits (ICs)
Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) - Voltage Dropout (Max) 0.23V @ 300mA Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) 90μA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3		PMIC - Voltage Regulators - Linear
Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.23V @ 300mACurrent - Output300mACurrent - Quiescent (Iq)90µACurrent - Supply (Max)90µAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Package	TO-243AA
Output TypeFixedNumber of Regulators1Voltage - Input (Max)5.5 VVoltage - Output (Min/Fixed)3.3 VVoltage - Output (Max)-Voltage Dropout (Max)0.23 V @ 300mACurrent - Output300mACurrent - Quiescent (Iq)90μACurrent - Supply (Max)90μAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Series	-
Number of Regulators Voltage - Input (Max) Voltage - Output (Min/Fixed) 3.3V Voltage - Output (Max) Voltage Dropout (Max) Current - Output 300mA Current - Quiescent (Iq) 90µA Current - Supply (Max) 90µA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature 40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package	Output Configuration	Positive
Voltage - Input (Max)5.5 VVoltage - Output (Min/Fixed)3.3 VVoltage - Output (Max)-Voltage Dropout (Max)0.23 V @ 300mACurrent - Output300mACurrent - Quiescent (Iq)90μACurrent - Supply (Max)90μAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Output Type	Fixed
Voltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.23V @ 300mACurrent - Output300mACurrent - Quiescent (Iq)90μACurrent - Supply (Max)90μAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Number of Regulators	1
Voltage - Output (Max) Voltage Dropout (Max) Current - Output 300mA Current - Quiescent (Iq) Current - Supply (Max) PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package	Voltage - Input (Max)	5.5V
Voltage Dropout (Max) Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package	Voltage - Output (Min/Fixed)	3.3V
Current - Output 300mA Current - Quiescent (Iq) 90μA Current - Supply (Max) 90μA PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Voltage - Output (Max)	-
Current - Quiescent (Iq)90μACurrent - Supply (Max)90μAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Voltage Dropout (Max)	0.23V @ 300mA
Current - Supply (Max)90μAPSRR70dB ~ 65dB (100Hz ~ 1kHz)Control FeaturesEnableProtection FeaturesOver Current, Over Temperature, Short CircuitOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / CaseTO-243AASupplier Device PackageSOT-89-3	Current - Output	300mA
PSRR 70dB ~ 65dB (100Hz ~ 1kHz) Control Features Enable Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Current - Quiescent (Iq)	90μΑ
Control Features Protection Features Over Current, Over Temperature, Short Circuit -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Current - Supply (Max)	90μΑ
Protection Features Over Current, Over Temperature, Short Circuit Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	PSRR	70dB ~ 65dB (100Hz ~ 1kHz)
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Control Features	Enable
Mounting Type Surface Mount Package / Case TO-243AA Supplier Device Package SOT-89-3	Protection Features	Over Current, Over Temperature, Short Circuit
Package / Case TO-243AA Supplier Device Package SOT-89-3	Operating Temperature	-40°C ~ 85°C
Supplier Device Package SOT-89-3	Mounting Type	Surface Mount
	Package / Case	TO-243AA
Report errors?	Supplier Device Package	SOT-89-3
		Report errors?

PAM3101HCA330 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PAM3101HCA330 Payment Methods



















PAM3101HCA330 Shipping Methods













If you have any question about PAM3101HCA330, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com